

VH 12.5/5/3.4



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Connecting sleeve (terminal), when screwed in, Width: 5 mm, Height: 5 mm, Depth: 12.5 mm, Number of poles: 1, Copper	
Order No.	0300800000	
Туре	VH 12.5/5/3.4	
GTIN (EAN)	4008190056179	
Qty.	50 items	



VH 12.5/5/3.4



Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals				
ROHS	Conform			
Dimensions and weights				
Depth	12.5 mm	Depth (inches)	0.4921 inch	
Height	5 mm	Height (inches)	0.1968 inch	
Width	5 mm	Width (inches)	0.1968 inch	
Diameter	5.5 mm	Net weight	1.11 g	
Temperatures				
Storage temperature	-25 °C55 °C	Ambient temperature	-5 °C40 °C	
Environmental Product Comp	liance			
RoHS Compliance Status	Compliant with exemption			
RoHS Exemption (if applicable/known)	6c			
REACH SVHC	Lead 7439-92-1			
SCIP	73c55621-8329-401d-bde2-7fd78e0e60e4			
Material data				
Basic material	Copper	Colour	grey	
System specifications			<u>'</u>	
Version	for cross-connection link			
Additional technical data				
Type of fixing	when screwed in	Installation advice	Direct mounting	
Dimensions				
Diameter	5.5 mm	TS 32 offset	32.5 mm	
General				
Number of poles	1	Installation advice	Direct mounting	
Classifications				
ETIM 8.0	EC002848	ETIM 9.0	EC002848	
ETIM 10.0	EC002848	ECLASS 14.0	27-25-03-90	
ECLASS 15.0	27-25-03-90			

Catalogue status / Drawings