

Q 4 SAK6N



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Cross-connector (terminal), when screwed in, grey, 41 A, Number of poles: 4, Pitch in mm (P): 7.90, Insulated: No, Width: 29.7 mm		
0456900000		
Q 4 SAK6N		
4008190032579		
50 items		



Q 4 SAK6N



Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals			
DOLLO	0 1		
ROHS	Conform		
Dimensions and weights			
Depth	20.5 mm	Depth (inches)	0.8071 inch
Height	6 mm	Height (inches)	0.2362 inch
Vidth	29.7 mm	Width (inches)	1.1693 inch
let weight	9.52 g		,
Temperatures			
Storage temperature	-25 °C55 °C	Ambient temperature	-5 °C40 °C
Environmental Product Cor	npliance		
PaUC Campliance Status	Compliant without ava	matian	
RoHS Compliance Status REACH SVHC	Compliant without exemption No SVHC above 0.1 wt%		
	140 OVIIO above 0.1 WI	.,,	
Material data	'		
Basic material	CuSn	Colour	grey
System specifications			
/ersion	for cross-connection link		
Additional technical data			
Type of fixing	when screwed in	Installation advice	Direct mounting
Explosion-tested version	No	Installation advice	Direct mounting
	110		
Dimensions			
Pitch in mm (P)	7.90 mm		
General			
Number of poles	4	Installation advice	Direct mounting
Rating data			
Rated voltage	400 V	Nominal current	41 A
Classifications			
ETIM 8.0	EC000489	ETIM 9.0	EC000489
ETIM 10.0	EC000489	ECLASS 14.0	27-25-03-03

Catalogue status / Drawings