

Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Fuse terminal blocks and component terminal blocks allow protective and functional elements to be integrated directly into the terminal strip. Fuse terminal blocks include built-in fuse holders to reliably protect electrical circuits against overload—ideal for control and distribution systems. Component terminal blocks make it possible to incorporate electronic components such as diodes, resistors, or LEDs directly into the wiring. This enables space-saving and clearly arranged implementation of switching functions and signal separation. Both types of terminal blocks ensure higher safety, easy maintenance, and a compact, function-oriented installation.

General ordering data

Version	Fuse terminal, Screw connection, medium yellow, $10\ mm^2$, $10\ A$, $500\ V$, Number of connections: 2, Number of levels: 1, TS 35
Order No.	<u>0501520000</u>
Туре	SAKS 1/35/G25
GTIN (EAN)	4008190047801
Qty.	20 items





Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

A		- COLONIA DE COLONIA D	
Approvals	(€®	R SI	
ROHS	Conform	DEVICE N. St	
UL File Number Search	<u>UL Website</u>		
Certificate No. (UR)	E60693		
Dimensions and weights			
Depth	53 mm	Depth (inches)	2.0866 inch
Height	54 mm	Height (inches)	2.126 inch
Width	13 mm	Width (inches)	0.5118 inch
Net weight	38.3 g		0.0 1 70 111011
Temperatures			
			·
Storage temperature	-25 °C55 °C	Ambient temperature	-5 °C40 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C
Environmental Product Com	oliance		
RoHS Compliance Status	Compliant without exemptio	n	
REACH SVHC	No SVHC above 0.1 wt%	•	
Material data			
Dania wastavial	V-C	Calaur	ma a aliuma u a llauu
Basic material	KrG	Colour	medium yellow
<u> </u>	V-0, 5VA		1
· · · · · · ·	V-U, 5VA		
System specifications	Screw connection, Fuse cartridge, One end without connector	End cover plate required	Yes
System specifications /ersion	Screw connection, Fuse cartridge, One end without	End cover plate required Number of levels	Yes
System specifications Version Number of potentials	Screw connection, Fuse cartridge, One end without connector		
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally	Screw connection, Fuse cartridge, One end without connector 1 2 No	Number of levels	1
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail	Screw connection, Fuse cartridge, One end without connector	Number of levels Number of potentials per tier PE connection N-function	1 1 No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail	Screw connection, Fuse cartridge, One end without connector 1 2 No	Number of levels Number of potentials per tier PE connection	1 1 No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35	Number of levels Number of potentials per tier PE connection N-function	1 1 No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35	Number of levels Number of potentials per tier PE connection N-function PEN function	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No	Number of levels Number of potentials per tier PE connection N-function PEN function Number of similar terminals	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides Installation advice	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No right Direct mounting	Number of levels Number of potentials per tier PE connection N-function PEN function	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides Installation advice Type of mounting	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No	Number of levels Number of potentials per tier PE connection N-function PEN function Number of similar terminals	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides Installation advice Type of mounting	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No right Direct mounting	Number of levels Number of potentials per tier PE connection N-function PEN function Number of similar terminals	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides Installation advice Type of mounting CSA rating data	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No right Direct mounting	Number of levels Number of potentials per tier PE connection N-function PEN function Number of similar terminals Explosion-tested version	1 1 No No No
System specifications Version Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides Installation advice Type of mounting CSA rating data Wire cross section max. (CSA) Current size C (CSA)	Screw connection, Fuse cartridge, One end without connector 1 2 No TS 35 No right Direct mounting Snap-on	Number of levels Number of potentials per tier PE connection N-function PEN function Number of similar terminals	1 1 No No No

Creation date 04.12.2025 02:30:13 MEZ

Wire cross section min. (CSA)

Catalogue status / Drawings

26 AWG





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.	10 mm²	Connection type, additional connection	Screw connection
Conductors for clamping (rate	ed connection)		
O	D.C.	Mina annualities annualities ANA/C	AVA/C 10
Gauge to IEC 60947-1	B6	Wire connection cross section AWG, max.	AWG 10
Connection direction	on side	Tightening torque, max.	2.4 Nm
Γightening torque, min.	1.2 Nm	Stripping length	12 mm
Гуре of connection 2	Screw connection	Type of connection	Screw connection
Number of connections	2	Clamping range, max.	16 mm ²
Clamping range, min.	0.13 mm ²	Clamping screw	M 4
Blade size	1.0 x 5.5 mm	Wire connection cross section AWG, min.	AWG 26
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.13 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	10 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.13 mm ²	Wire connection cross section, finely stranded, max.	10 mm²
Wire connection cross section, finely stranded, min.	0.13 mm ²	Connection cross-section, stranded, max.	10 mm ²
Connection cross-section, stranded, mir	n. 0.13 mm²	Torque level with DMS electric screwdriver	4
Wire connection cross-section, solid core, max.	16 mm²	Wire connection cross-section, solid core, min.	0.13 mm ²
Connection cross-section, finely stranded, min.	0.13 mm ²		
General			
Wire connection cross section AWG, max.	AWG 10	Installation advice	Direct mounting
Wire connection cross section AWG, min.	AWG 26	Standards	IEC 60947-7-3
Mounting rail	TS 35		
Rating data			
Rated cross-section	10 mm²	Rated voltage	500 V
Rated DC voltage	500 V	Nominal current	10 A
Current at maximum wires	10 A	Standards	IEC 60947-7-3
Volume resistance according to IEC 60947-7-x	0.56 mΩ	Rated impulse withstand voltage	6 kV
Power loss in accordance with IEC 60947-7-x	1.82 W	Pollution severity	3
UL rating data			
		0.00	
Conductor size Factory wiring max. (UR	<u>' </u>	Current size C (UR)	6.3 A
Voltage size C (UR)	600 V	Conductor size Factory wiring min. (UR)	
			00 41440
Certificate No. (UR) Conductor size Field wiring max. (UR)	E60693 10 AWG	Conductor size Field wiring min. (UR)	22 AWG

Creation date 04.12.2025 02:30:13 MEZ

Product information

Catalogue status / Drawings

The voltage depends on the selected fuse element or the selected indicator light





Weidmüller Interface GmbH & Co. KG

4

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Classifications

ETIM 8.0	EC000899	ETIM 9.0	EC000899
ETIM 10.0	EC000899	ECLASS 14.0	27-25-01-13
ECLASS 15.0	27-25-01-13		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Cross-connections









The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Туре	QL 2 SAKS1	Version
Order No.	0191400000	Cross-connector (terminal), when screwed in, grey, 47 A, Number of
GTIN (EAN)	4008190123130	poles: 2, Pitch in mm (P): 13.00, Insulated: No, Width: 18.9 mm
Qty.	50 ST	
Туре	QL 3 SAKS1	Version
Type Order No.	QL 3 SAKS1 0191500000	Version Cross-connector (terminal), when screwed in, grey, 47 A, Number of

Disconnect plugs



In contrast to the terminal blocks with integrated disconnect lever, our disconnect plugs can be completely detached or removed from the terminal block and the respective application and offer a flexible alternative solution to our standard disconnectors.

General ordering data

	- · · · · · · · · · · · · · · · · · · ·	
Туре	QL 4 SAKS1	Version
Order No.	<u>0191600000</u>	Cross-connector (terminal), when screwed in, grey, 47 A, Number of
GTIN (EAN)	4008190105518	poles: 4, Pitch in mm (P): 13.00, Insulated: No, Width: 44.7 mm
Qty.	20 ST	

Cross-connections









The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

General ordering data

Туре	QL 10 SAKS1	Version
Order No.	0338800000	Cross-connector (terminal), when screwed in, grey, 36 A, Number of
GTIN (EAN)	4008190127039	poles: 10, Pitch in mm (P): 13.00, Insulated: No, Width: 122.1 mm
Qty.	20 ST	

End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

General ordering data

Туре	AP SAKS1+3 KRG	Version
Order No.	0191320000	End plate for terminals, dark beige, yellow, Height: 54 mm, Width: 3
GTIN (EAN)	4008190031688	mm, V-0, KrG, Snap-on: Yes
Qty.	20 ST	
Туре	AP SAKS1+3 KRG/DB	Version
Type Order No.	AP SAKS1+3 KRG/DB 0191300000	Version End plate for terminals, dark beige, Height: 54 mm, Width: 3 mm, V-0,
	·	

Mounting support



We offer a broad portfolio of mounting support for easy handling and supplementation of our products. From various tools to insulating sleeves and various screws, our components are matched to each other down to the last detail and thus facilitate assembly in compliance with the respective standards and protective regulations.

General ordering data

Type	KISC M3X6 SAKS1	Version
Order No.	0346200000	Clamping yoke, Mounting screw, Steel
GTIN (EAN)	4008190175658	
Qty.	100 ST	

Creation date 04.12.2025 02:30:13 MEZ



Weidmüller Interface GmbH & Co. KG

7

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Fuse







As accessories for our wide product portfolio of fuse terminal blocks, we also offer the appropriate fuse links. The portfolio includes device protection fuses (miniature fuses) from 5x20 mm up to 10x38 mm, E 14 to E 18 fuse links, as well as automotive fuses and automatic circuit breakers. Gauge rings for the fuse holders round off the overall portfolio.

General ordering data

Туре	G 25/0.25A/M GE	Version
Order No.	0546900000	Miniature fuse, medium time-lag, 0.25 A, G-Si. 5 x 25
GTIN (EAN)	4008190097370	
Qty.	10 ST	
Туре	G 25/0.50A/M WS	Version
Order No.	0510300000	Miniature fuse, medium time-lag, 0.5 A, G-Si. 5 x 25
GTIN (EAN)	4008190018368	
Qty.	10 ST	
Туре	G 25/0.80A/M GR	Version
Order No.	0646400000	Miniature fuse, medium time-lag, 0.8 A, G-Si. 5 x 25
GTIN (EAN)	4008190060794	
Qty.	10 ST	
Туре	G 25/1.00A/M RT	Version
Order No.	0265800000	Miniature fuse, medium time-lag, 1 A, G-Si. 5 x 25
GTIN (EAN)	4008190141660	
Qty.	10 ST	
Туре	G 25/2.00A/F BL	Version
Order No.	0192700000	Miniature fuse, quick-acting, 2 A, G-Si. 5 x 25
GTIN (EAN)	4008190176402	
Qty.	10 ST	
Туре	G 25/4.00A/F BR	Version
Order No.	0192800000	Miniature fuse, quick-acting, 4 A, G-Si. 5 x 25
GTIN (EAN)	4008190115319	
Qty.	10 ST	
Туре	G 25/6.30A/F GN	Version
Order No.	0192900000	Miniature fuse, quick-acting, 6.3 A, G-Si. 5 x 25
GTIN (EAN)	4008190135461	
Qty.	10 ST	
Туре	G 25/10.0A/M RT	Version
Order No.	0193100000	Miniature fuse, medium time-lag, 10 A, G-Si. 5 x 25
GTIN (EAN)	4008190023799	
Qty.	10 ST	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/5 MC NE WS
Order No. 1609801044
GTIN (EAN) 4008190397111
Qty. 1000 ST

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white

Testadapter and testsockets









Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Type PS 4 F.STB 4
Order No. 0299600000
GTIN (EAN) 4008190074043
Oty. 20 ST

Version

Test adapter (terminal), 230 V

Creation date 04.12.2025 02:30:13 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

Type SCHT 7
Order No. 0517960000
GTIN (EAN) 4008190001742
Oty. 20 ST

Version

SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00

Weidmueller, white

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6.5 MC SDR	Version
Order No.	1609850000	Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50
GTIN (EAN)	4008190456610	Weidmueller, To customer specification
Qty.	180 ST	

Creation date 04.12.2025 02:30:13 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6.5 MC NE WS
Order No.	1609840000
GTIN (EAN)	4008190203429
Qty.	900 ST

Version

Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Weidmueller, white

End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

General ordering data

Туре	WTW EN	Version
Order No.	<u>1058800000</u>	Partition plate (terminal), dark beige, Height: 86 mm, Width: 3 mm,
GTIN (EAN)	4008190140175	V-0, Wemid
Qty.	20 ST	

Slotted screwdriver



Slotted screwdriver with rounded blade SD DIN 5265, ISO 2380/2, output to DIN 5264, ISO 2380/1. ChromTop tip, SoftFinish grip

Creation date 04.12.2025 02:30:13 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

General ordering data

Type SDS 1.0X5.5X150
Order No. 9008350000
GTIN (EAN) 4032248056316

Screwdriver, Screwdriver

Version

End bracket

Qty.









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Type WEW 32/1
Order No. 1067600000
GTIN (EAN) 4008190099657
Oty. 50 ST

End bracket, dark beige, TS 32, V-2, PA 66 GF 30, Width: 12 mm,

100 °C

Version

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

11

General ordering data

800 ST

Qty.

 Type
 DEK 5/8 MC NE WS
 Version

 Order No.
 1856740000
 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

 GTIN (EAN)
 4032248400850
 Weidmueller, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 MC SDR
Order No.	<u>1856750000</u>
GTIN (EAN)	4032248400867
Qty.	160 ST

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 PLUS MC NE WS	Version
Order No.	1046350000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248782055	Weidmueller, white
Qty.	800 ST	

Creation date 04.12.2025 02:30:13 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 PLUS MC SDR
Order No.	<u>1046370000</u>
GTIN (EAN)	4032248782079
Qty.	160 ST

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification

DEK 5/8



WS/DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/8 MM WS	Version
Order No.	2007130000	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 ST	

Creation date 04.12.2025 02:30:13 MEZ





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Marker holder

The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Туре	BZT 1 WS 10/5	Version
Order No.	<u>1805490000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Туре	BZT 1 ZA WS 10/5	Version
Order No.	1805520000	Accessories, Marker holder
GTIN (EAN)	4032248270248	