


DEK 5 GW O**Weidmüller Interface GmbH & Co. KG**Klingenbergsstraße 26
D-32758 Detmold
Germanywww.weidmueller.com

The dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a large range of ready-printed markers. Strips for fast installation in one work step. The printing is easy to read, rich in contrast, and is available in five widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank cards, MultiCard or as cards with standard printing

General ordering data

Version	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 Weidmüller, white
Order No.	0522761035
Type	DEK 5 GW O
GTIN (EAN)	4008190184360
Qty.	500 items

DEK 5 GW O

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

RoHS	Conform
------	---------

Dimensions and weights

Height	5 mm	Height (inches)	0.1968 inch
Width	5 mm	Width (inches)	0.1968 inch
Net weight	0.04 g		

Temperatures

Operating temperature range	-40...100 °C
-----------------------------	--------------

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%
Product Carbon Footprint	Cradle to gate 0.001 kg CO2 eq.

General data

Material colour according to resistance code	9
--	---

Orientation of print	horizontal
----------------------	------------

Printing method	MC Laser
-----------------	----------

Width	5 mm
-------	------

UL 94 flammability rating	V-2
---------------------------	-----

Operating temperature range, max.	100 °C
-----------------------------------	--------

Operating temperature range, min.	-40 °C
-----------------------------------	--------

Colour	white
--------	-------

Halogen	No
---------	----

Basic material	Polyamide 66
----------------	--------------

Colour of printing	black
--------------------	-------

Printed characters	Upper-case letters
--------------------	--------------------

Number of markers per packaging unit	Form of supply	Card
--------------------------------------	----------------	------

Number of markers per combination	1 Card = Terminal marker
-----------------------------------	--------------------------

Operating temperature range	-40...100 °C
-----------------------------	--------------

Application/manufacturer	Weidmüller
--------------------------	------------

Connector markers

Pitch in mm (P)	5.00 mm
-----------------	---------

Classifications

ETIM 8.0	EC000761	ETIM 9.0	EC000761
ETIM 10.0	EC000761	ECLASS 14.0	27-28-11-01
ECLASS 15.0	27-28-11-01		