



In contrast to the terminal blocks with integrated disconnect lever, our disconnect plugs can be completely detached or removed from the terminal block and the respective application and offer a flexible alternative solution to our standard disconnectors.

**General ordering data**

Version	Cross-connector (terminal), when screwed in, grey, 27 A, Number of poles: 75, Pitch in mm (P): 6.00, Insulated: No, Width: 0.8 mm
Order No.	<a href="#">0535200000</a>
Type	QB 75/6.2/15
GTIN (EAN)	4008190179168
Qty.	10 items

**Technical data****Approvals**

RoHS	Conform
------	---------

**Dimensions and weights**

Depth	17.5 mm	Depth (inches)	0.689 inch
Height	461.3 mm	Height (inches)	18.1614 inch
Width	0.8 mm	Width (inches)	0.0315 inch
Net weight	26.26 g		

**Temperatures**

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
---------------------	----------------	---------------------	---------------

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Material data**

Basic material	Copper	Colour	grey
----------------	--------	--------	------

**System specifications**

Version	for cross-connection link
---------	---------------------------

**Additional technical data**

Type of fixing	when screwed in	Installation advice	Direct mounting
Explosion-tested version	No		

**Dimensions**

Pitch in mm (P)	6.00 mm
-----------------	---------

**General**

Number of poles	75	Installation advice	Direct mounting
-----------------	----	---------------------	-----------------

**Rating data**

Nominal current	27 A
-----------------	------

**Classifications**

ETIM 8.0	EC000489	ETIM 9.0	EC000489
ETIM 10.0	EC000489	ECLASS 14.0	27-25-03-03
ECLASS 15.0	27-25-03-03		

## Accessories

### Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

### General ordering data

Type	ISPF QB75 SW	Version
Order No.	<a href="#">052670000</a>	Insulation profile, Plastic, black
GTIN (EAN)	4008190093723	
Qty.	10 ST	
Type	ISPF QB75 RT	Version
Order No.	<a href="#">052676000</a>	Insulation profile, Plastic, red
GTIN (EAN)	4008190157821	
Qty.	10 ST	
Type	ISPF QB75 BL	Version
Order No.	<a href="#">052678000</a>	Insulation profile, Plastic, blue
GTIN (EAN)	4008190093105	
Qty.	10 ST	