

ISPF QB58 RT



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

	·		
Version	Insulation profile, PVC, red		
Order No.	<u>0546040000</u>		
Туре	ISPF QB58 RT		
GTIN (EAN)	4008190497941		
Qty.	10 items		



ISPF QB58 RT



Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals				
ROHS	Conform			
Dimensions and weights				
Depth	5.7 mm	Depth (inches)	0.2244 inch	
Height	465 mm	Height (inches)	18.3071 inch	
Width	2.5 mm	Width (inches)	0.0984 inch	
Net weight	6.08 g			
Temperatures			,	
Ambient temperature	-5 °C40 °C			
Environmental Product C	compliance		<u>'</u>	
RoHS Compliance Status	Compliant without exemption			
REACH SVHC	No SVHC above 0.1 wt%			
Material data				
Basic material	PVC	Colour	red	
UL 94 flammability rating	V-0			
System specifications	,		,	
Version	Cover profile			
Additional technical data	1			
Type of fixing	Plugged	Installation advice	Direct mounting	
Explosion-tested version	No	Type of mounting	Plugged	
General				
Installation advice	Direct mounting			
Classifications				
Viassiiivativiis				
ETIM 8.0	EC002848	ETIM 9.0	EC002848	
ETIM 10.0	EC002848	ECLASS 14.0	27-25-03-90	
ECLASS 15.0	27-25-03-90			

Catalogue status / Drawings