

Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Earth-wire disconnect terminal helps detect earth faults and enables the earthing of the auxiliary circuit to be disconnected. The different kind of operation status is indicated by a red and green LED.

General ordering data

Version	Test-disconnect terminal, Screw connection, medium yellow, 4 mm ² , 27 A, 60 V, Number of connections: 2, Number of levels: 1
Order No.	<u>0699020000</u>
Туре	SAKT E/32 2LD 60VAC
GTIN (EAN)	4008190090012
Qty.	5 items





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights Depth 53.5 mm Depth (inches) 2.1063 inch Height (inches) 2.591 inch Width (inches) 2.591 inch Widt				
Dimensions and weights Depth 53.5 mm	Approvals	(€		
Height 65 mm Height (inches) 2.5591 inch Width 19 mm Width (inches) 0.748 inch Width (inches) 0.	ROHS	Conform		
Height 65 mm Height (inches) 2.5591 inch Width (19 mm) Width (inches) 0.748 inch Width (inches)	Dimensions and weights			
Height 65 mm Height (inches) 2.5591 inch Width 19 mm Width (inches) 0.748 inch Width (inches) 0.	Depth	53.5 mm	Depth (inches)	2.1063 inch
Width 19 mm				
Temperatures Storage temperature -25 °C55 °C Ambient temperature -5 °C40 °C Continuous operating temp., min60 °C Continuous operating temp., max. 130 °C Environmental Product Compliance RoHS Compliance Status Compliant with exemption RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of potentials 1 Number of clamping points per level 4 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No No PEN function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	Width			
Storage temperature -25 °C55 °C Ambient temperature -5 °C40 °C Continuous operating temp., min60 °C Continuous operating temp., max. 130 °C Environmental Product Compliance RoHS Compliance Status Compliant with exemption RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Material data KrG Colour medium yellow U. 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No No PEN function No No Additional technical data Open sides right Installation advice Direct mounting				
Continuous operating temp., min60 °C Continuous operating temp., max. 130 °C Environmental Product Compliance RoHS Compliance Status Compliant with exemption RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No Additional technical data Open sides right Installation advice Direct mounting	Temperatures			
Continuous operating temp., min60 °C Continuous operating temp., max. 130 °C Environmental Product Compliance RoHS Compliance Status Compliant with exemption RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No Additional technical data Open sides right Installation advice Direct mounting	Storage temperature	25 °C 55 °C	Ambient temperature	5 °C 40 °C
RoHS Compliance Status Compliant with exemption RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of potentials 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No PE function No PEN function No Additional technical data Compliant with exemption Colour medium yellow Medium yellow Medium yellow Pes Colour medium yellow			· · · · · · · · · · · · · · · · · · ·	
RoHS Compliance Status RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of clamping points per level 4 Levels cross-connected internally Ves Mounting rail TS 32 No No PE function No Additional technical data Count medium yellow Colour medium yellow Medium yell	community temps, min.		Committees operating temp., max.	100 0
RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	Environmental Product Comp	liance		
RoHS Exemption (if applicable/known) 7a, 7cl REACH SVHC Lead 7439-92-1 SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	RoHS Compliance Status	Compliant with exemption		
REACH SVHC SCIP 999cd67e-471e-4085-8dba-1342fcea86de Material data Basic material UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail TS 32 N-function No Additional technical data Needium yellow Colour Medium yellow Mediu				
Material data Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data National very plate required Yes Number of levels 1 Number of potentials per tier 1 PE connection No No PEN function No Direct mounting				
Basic material KrG Colour medium yellow UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No Additional technical data Colour medium yellow Medium yellow Test of cover plate required Yes Number of levels 1 Number of potentials per tier 1 PE connection No No PEN function No Direct mounting				
UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail TS 32 N-function No Additional technical data Ves End cover plate required Yes Number of levels 1 Number of potentials per tier 1 PE connection No No PEN function No Direct mounting	Material data			
UL 94 flammability rating V-0, 5VA System specifications Version Screw connection, Spacer, with LED Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail TS 32 N-function No Additional technical data Ves End cover plate required Yes Number of levels 1 Number of potentials per tier 1 PE connection No No PEN function No Direct mounting	Pasio material	KrC	Colour	modium vollow
System specifications Version Screw connection, Spacer, with LED Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail TS 32 PE function No Additional technical data Screw connection, Spacer, with LED Number of potential required Number of levels 1 Number of potentials per tier 1 PE connection No No PEN function No Direct mounting			Coloui	medium yellow
Version Screw connection, Spacer, with LED Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail TS 32 Nober of potentials per tier Number of potentials per tier Number of potentials per tier Nober of clamping points per level Fe connection No No PEN function No Additional technical data Open sides Pirect mounting		V-0, 5VA		
with LED Number of potentials 1 Number of levels 1 Number of clamping points per level 4 Number of potentials per tier 1 Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data Open sides Fight Installation advice Direct mounting	System specifications			
Number of clamping points per level 4 Levels cross-connected internally Mounting rail TS 32 N-function No PE function No Additional technical data Open sides Number of potentials per tier 1 PE connection No No PEN function No Direct mounting				
Levels cross-connected internally Yes PE connection No Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	Version	Screw connection, Spacer, with LED	End cover plate required	Yes
Mounting rail TS 32 N-function No PE function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	Number of potentials	with LED	Number of levels	
PE function No PEN function No Additional technical data Open sides right Installation advice Direct mounting	Number of potentials	with LED	Number of levels	1
Additional technical data Open sides right Installation advice Direct mounting	Number of potentials Number of clamping points per level	with LED 1 4 Yes	Number of levels Number of potentials per tier PE connection	1
Open sides right Installation advice Direct mounting	Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail	with LED 1 4 Yes TS 32	Number of levels Number of potentials per tier PE connection N-function	1 1 No No
	Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail	with LED 1 4 Yes TS 32	Number of levels Number of potentials per tier PE connection N-function	1 1 No No
	Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function	with LED 1 4 Yes TS 32	Number of levels Number of potentials per tier PE connection N-function	1 1 No No
Type of mounting Shap-on	Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data	with LED 1 4 Yes TS 32 No	Number of levels Number of potentials per tier PE connection N-function PEN function	1 1 No No No
	Number of potentials Number of clamping points per level Levels cross-connected internally Mounting rail PE function Additional technical data Open sides	with LED 1 4 Yes TS 32 No	Number of levels Number of potentials per tier PE connection N-function PEN function	1 1 No No No

Creation date 26.11.2025 03:43:25 MEZ

Gauge to IEC 60947-1

Connection direction

Conductors for clamping (rated connection)

Α5

on side

Catalogue status / Drawings

max.

Type of connection 2

Wire connection cross section AWG,

AWG 8

Screw connection

2





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Type of connection	Screw connection	Number of connections	2
Clamping range, max.	10 mm ²	Clamping range, min.	0.5 mm ²
Clamping screw	M 3.5	Blade size	4.0 x 0.8 mm
Wire connection cross section AWG, min.	AWG 22	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	6 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	6 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm ²	Wire connection cross section, finely stranded, max.	6 mm²
Wire connection cross section, finely stranded, min.	0.5 mm ²	Connection cross-section, stranded, max.	6 mm ²
Connection cross-section, stranded, mi	n. 0.5 mm²	Wire connection cross-section, solid core, max.	10 mm²
Wire connection cross-section, solid core, min.	0.5 mm²	Connection cross-section, finely stranded, min.	0.5 mm²
General			
Wire connection cross section AWG, max.	AWG 8	Installation advice	Direct mounting
Wire connection cross section AWG, min.	AWG 22	Mounting rail	TS 32

Rating data

Rated cross-section	4 mm ²	Rated voltage	60 V
Rated DC voltage	0 V	Nominal current	27 A
Current at maximum wires	27 A	Volume resistance according to IEC 60947-7-x	1 mΩ
Power loss in accordance with IEC 60947-7-x	1.02 W	Pollution severity	3

Classifications

ETIM 6.0	EC000902	ETIM 7.0	EC000902
ETIM 8.0	EC000902	ETIM 9.0	EC000902
ETIM 10.0	EC000902	ECLASS 9.0	27-14-11-26
ECLASS 9.1	27-14-11-26	ECLASS 10.0	27-14-11-26
ECLASS 11.0	27-14-11-26	ECLASS 12.0	27-14-11-26
ECLASS 13.0	27-25-01-09	ECLASS 14.0	27-25-01-09
ECLASS 15.0	27-25-01-09		





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

End bracket









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Type EW 35 Version Order No. 0383560000 End bracket, beige, TS 35, V-2, Wemid, Width: 8.5 mm, 100 °C 4008190181314

GTIN (EAN) 50 ST

Qty. Туре

Order No. GTIN (EAN)

Qty.

EWK 1

0206160000 4008190080020

50 ST

Version

End bracket, beige, TS 32, V-0, Wemid, Width: 9 mm, 100 °C

Testadapter and testsockets









Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

20 ST

Туре PS 2.3 RT Order No. 0180400000 Test adapter (terminal), 230 V, 20 mA GTIN (EAN) 4008190060121

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 MC SDR
Order No.	<u>1609810000</u>
GTIN (EAN)	4008190456597
Qty.	200 ST

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, To customer specification

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 MC NE WS	Version
Order No.	1609801044	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1000 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6 MC SDR
Order No.	1609830000
GTIN (EAN)	4008190456603
Qty.	200 ST

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/6 MC NE WS	Version
Order No.	1609820000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190203436	Weidmueller, white
Qty.	1000 ST	
Туре	DEK 5/6.5 MC NE WS	Version
Type Order No.	DEK 5/6.5 MC NE WS 1609840000	Version Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/6.5 MC SDR
Order No. 1609850000
GTIN (EAN) 4008190456610
Qty. 180 ST

Version

Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Weidmueller, To customer specification

Testadapter and testsockets









Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Type PS 4 F Order No. 02996 GTIN (EAN) 4008 Oty. 20 ST

PS 4 F.STB 4
0299600000
4008190074043

Version

Test adapter (terminal), 230 V

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 MC NE WS
Order No.	1856740000
GTIN (EAN)	4032248400850
Qty.	800 ST

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/8 MC SDR	Version
Order No.	1856750000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	WS 8/5 MC NE WS
Order No.	<u>1640740000</u>
GTIN (EAN)	4008190279103
Qty.	720 ST

Version

WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Allen-Bradley, white

End bracket









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Туре	EW 35 GR 7032	Version
Order No.	0383530000	End bracket, grey, TS 35, V-0, Wemid, Width: 9 mm, 120 °C
GTIN (EAN)	4008190027322	
Qty.	50 ST	
Туре	EW 35/SCHA/M3	Version
Order No.	0258660000	End bracket, beige, TS 35, V-2, Wemid, Width: 16.5 mm, 100 °C
GTIN (EAN)	4008190033477	
Qty.	20 ST	
Туре	WEW 35/1	Version
Type Order No.	WEW 35/1 1059000000	Version End bracket, dark beige, TS 35, V-2, Wemid, Width: 12 mm, 100 °C
	'	
Order No.	1059000000	
Order No. GTIN (EAN)	1059000000 4008190172282	
Order No. GTIN (EAN) Oty.	1059000000 4008190172282 50 ST	End bracket, dark beige, TS 35, V-2, Wemid, Width: 12 mm, 100 °C
Order No. GTIN (EAN) Oty. Type	1059000000 4008190172282 50 ST WEW 35/2	End bracket, dark beige, TS 35, V-2, Wemid, Width: 12 mm, 100 °C Version

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Type	ZEW 35	Version
Order No.	9540000000	End bracket, dark beige, TS 35, V-2, Wemid, Width: 6 mm, 100 °C
GTIN (EAN)	4008190956264	
Qty.	20 ST	
Туре	ZEW 35/2	Version
Type Order No.	ZEW 35/2 8630740000	Version End bracket, dark beige, TS 35, V-2, Wemid, Width: 8 mm, 100 °C
• •	,	

Testadapter and testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Туре	PS 2.0 OR	Version
Order No.	0293800000	Test adapter (terminal), 230 V, 20 mA
GTIN (EAN)	4008190042356	
Qty.	20 ST	

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/6 MC NE BL	Version
Order No.	<u>1238290000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118267327	Weidmueller, blue
Qty.	1000 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	DEK 5/6 MC NE BR	Version
Order No.	1454900000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118323313	Weidmueller, brown
Qty.	1000 ST	
Туре	DEK 5/6 MC NE GE	Version
Order No.	1238280000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118038750	Weidmueller, yellow
Qty.	1000 ST	
Туре	DEK 5/6 MC NE GN	Version
Order No.	1238310000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118271812	Weidmueller, green
Qty.	1000 ST	
Туре	DEK 5/6 MC NE GR	Version
Order No.	1238330000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118323306	Weidmueller, grey
Qty.	1000 ST	
Туре	DEK 5/6 MC NE OR	Version
Order No.	<u>1912090000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4032248540525	Weidmueller, orange
Qty.	1000 ST	

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/6 PLUS MC NE WS	Version
Order No.	1011320000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4032248717644	Weidmueller, white
Qty.	1000 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 DEK 5/6 PLUS MC SDR

 Order No.
 1038650000

 GTIN (EAN)
 4032248767908

 Qty.
 200 ST

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

DEK 5/6



WS/DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/6 MM WS	Version
Order No.	2007120000	Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white
GTIN (EAN)	4050118392104	
Qty.	600 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

DEK 5/8



WS/DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	DEK 5/8 MM WS	Version
Order No.	2007130000	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 ST	

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/8 PLUS MC NE WS	Version
Order No.	1046350000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248782055	Weidmueller, white
Qty.	800 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 DEK 5/8 PLUS MC SDR

 Order No.
 1046370000

 GTIN (EAN)
 4032248782079

160 ST

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification

Marker holder

Qty.



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Туре	BZT 1 WS 10/5	Version
Order No.	1805490000	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Туре	BZT 1 ZA WS 10/5	Version
Order No.	<u>1805520000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 ST	

Creation date 26.11.2025 03:43:25 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

WS 8/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

	9	
Туре	WS 8/5 MM WS	Version
Order No.	2007150000	WS, Terminal marker, 8 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392029	
Qty.	800 ST	

Creation date 26.11.2025 03:43:25 MEZ