

**HDC CM BUS SV GCA M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The ConCept-CSB module is a double module and takes up two slots in the ConCept module frame. The ConCept-CSB module consists of a module carrier that is capable of holding two contact carriers. The contact carrier is manufactured with a die-cast zinc alloy which provides it with excellent shielding capabilities. The crimp contacts are insulated from the contact carrier and mounted in a plastic insert. A variety of pole counts – 1, 4 and 8 poles – are available to ensure compatibility with a wide range of applications.

**General ordering data**

Version	Heavy-duty connectors, HDC insert, ConCept module
Order No.	<a href="#">1014080000</a>
Type	HDC CM BUS SV GCA M
GTIN (EAN)	4032248722624
Qty.	1 items

## HDC CM BUS SV GCA M

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

## Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (cURus) E92202

## Dimensions and weights

Depth	33.5 mm	Depth (inches)	1.3189 inch
Height	3.9 mm	Height (inches)	0.1535 inch
Width	21.5 mm	Width (inches)	0.8465 inch
Length	33.5 mm	Length (inches)	1.3189 inch
Net weight	9 g		

## Temperatures

Limit temperature -40 °C ... 70 °C

## Environmental Product Compliance

RoHS Compliance Status Compliant without exemption

REACH SVHC No SVHC above 0.1 wt%

## ConCept Pneumatic module

UL 94 flammability rating V-0 Colour Silver grey

## Dimensions

Width 21.5 mm Total length base 33.5 mm  
Height of plug 3.9 mm

## General data

Number of poles	0	Type of connection	without
UL 94 flammability rating	V-0	Colour	Silver grey
Plugging cycles	≥ 500	Type	Earth connection clamp
Basic material	Polycarbonate	Series	ConCept module
Rated voltage (DIN EN 61984)	0 V	Rated impulse voltage (DIN EN 61984)	0 kV
Rated current (DIN EN 61984)	0 A	Free from halogens	false
Low smoke acc. DIN EN 45545-2	Yes		

## Version

Type of connection without Conductor cross-section, max. 0 mm<sup>2</sup>  
Conductor cross-section, min. 0 mm<sup>2</sup> Basic material Polycarbonate

## Classifications

ETIM 8.0 EC000438 ETIM 9.0 EC000438  
ETIM 10.0 EC000438 ECLASS 14.0 27-44-02-18  
ECLASS 15.0 27-44-02-18