


**WDU 2.5 OR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Product image**

To feed through power, signal, and data is the classical requirement in electrical engineering and panel building. The insulating material, the connection system and the design of the terminal blocks are the differentiating features. A feed-through terminal block is suitable for joining and/or connecting one or more conductors. They could have one or more connection levels that are on the same potential or insulated against one another.

**General ordering data**

Version	Feed-through terminal block, Screw connection, orange, 2.5 mm <sup>2</sup> , 24 A, 800 V, Number of connections: 2
Order No.	<a href="#">1020060000</a>
Type	WDU 2.5 OR
GTIN (EAN)	4008190012809
Qty.	100 items

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

## Approvals

## Approvals



ROHS	Conform
UL File Number Search	<a href="#">UL Website</a>
Certificate No. (UR)	E60693
Certificate No. (cURusEX)	E184763

## Dimensions and weights

Depth	46.5 mm	Depth (inches)	1.8307 inch
Height	60 mm	Height (inches)	2.3622 inch
Width	5.1 mm	Width (inches)	0.2008 inch
Net weight	7.49 g		

## Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-60 °C...85 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

## Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%
Product Carbon Footprint	Cradle to gate 0,066 kg CO <sub>2</sub> eq.

## Material data

Basic material	Wemid	Colour	orange
UL 94 flammability rating	V-0		

## Rating data IECEx/ATEX

Certificate No. (ATEX)	DEMKO14ATEX1338U	Certificate No. (IECEx)	IECEXULD14.0005U
Max. voltage (ATEX)	690 V	Current (ATEX)	24 A
Wire cross section max. (ATEX)	2.5 mm <sup>2</sup>	Max. voltage (IECEx)	690 V
Current (IECEx)	24 A	Wire cross section max. (IECEx)	2.5 mm <sup>2</sup>
Marking EN 60079-7	Ex eb II C Gb	Ex 2014/34/EU label	II 2 G D

## System specifications

Version	Screw connection, for plug-in cross-connector, for screwable cross-	End cover plate required	Yes
---------	---	--------------------------	-----

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

	connection, One end without connector		
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Mounting rail	TS 35	N-function	No
PE function	No	PEN function	No

## Additional technical data

Open sides	right	Number of similar terminals	1
Explosion-tested version	Yes	Type of mounting	Snap-on

## CSA rating data

Wire cross section max. (CSA)	12 AWG	Voltage size C (CSA)	600 V
Current size C (CSA)	20 A	Certificate No. (CSA)	200039-1057876
Wire cross section min. (CSA)	26 AWG		

## Conductors for clamping (additional connection)

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.	2.5 mm <sup>2</sup>	Connection type, additional connection	Screw connection
---	---------------------	--	------------------

## Conductors for clamping (rated connection)

Wire connection cross section AWG, max.	AWG 12
Connection direction	on side
Stripping length	10 mm
Type of connection	Screw connection
Number of connections	2
Clamping range, max.	4 mm <sup>2</sup>
Clamping range, min.	0.05 mm <sup>2</sup>
Clamping screw	M 2.5
Wire connection cross section AWG, min.	AWG 30
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	2.5 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.05 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	2.5 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.05 mm <sup>2</sup>
Wire connection cross section, finely stranded, max.	4 mm <sup>2</sup>
Wire connection cross section, finely stranded, min.	0.05 mm <sup>2</sup>
Connection cross-section, stranded, max.	4 mm <sup>2</sup>
Connection cross-section, stranded, min.	0.05 mm <sup>2</sup>
Twin wire-end ferrules, max.	1.5 mm <sup>2</sup>
Twin wire-end ferrules, min.	0.5 mm <sup>2</sup>
Torque level with DMS electric screwdriver	1

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

Wire connection cross-section, solid core, max.	4 mm <sup>2</sup>																																																																																										
Wire connection cross-section, solid core, min.	0.05 mm <sup>2</sup>																																																																																										
Connection cross-section, finely stranded, min.	0.05 mm <sup>2</sup>																																																																																										
Clampable conductor	<table border="1"> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table></td></tr></table>	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	solid, H05(07) V-U	min.	0.5 mm <sup>2</sup>	max.	4 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	stranded, H07V-R	min.	1.5 mm <sup>2</sup>	max.	4 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	flexible, H05(07) V-K	min.	0.5 mm <sup>2</sup>	max.	2.5 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	solid, H05(07) V-U	min.	0.5 mm <sup>2</sup>	max.	4 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>																																																																																		
Type	solid, H05(07) V-U																																																																																										
min.	0.5 mm <sup>2</sup>																																																																																										
max.	4 mm <sup>2</sup>																																																																																										
nominal	2.5 mm <sup>2</sup>																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	stranded, H07V-R	min.	1.5 mm <sup>2</sup>	max.	4 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	flexible, H05(07) V-K	min.	0.5 mm <sup>2</sup>	max.	2.5 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm														
Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm																																																																																				
min.	10 mm																																																																																										
max.	10 mm																																																																																										
nominal	10 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																						
min.	0.4 Nm																																																																																										
max.	0.8 Nm																																																																																										
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>1.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>4 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	stranded, H07V-R	min.	1.5 mm <sup>2</sup>	max.	4 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>																																																																																		
Type	stranded, H07V-R																																																																																										
min.	1.5 mm <sup>2</sup>																																																																																										
max.	4 mm <sup>2</sup>																																																																																										
nominal	2.5 mm <sup>2</sup>																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	flexible, H05(07) V-K	min.	0.5 mm <sup>2</sup>	max.	2.5 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																												
Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm																																																																																				
min.	10 mm																																																																																										
max.	10 mm																																																																																										
nominal	10 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																						
min.	0.4 Nm																																																																																										
max.	0.8 Nm																																																																																										
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>0.5 mm<sup>2</sup></td> </tr> <tr> <td>max.</td> <td>2.5 mm<sup>2</sup></td> </tr> <tr> <td>nominal</td> <td>2.5 mm<sup>2</sup></td> </tr> </table>	Type	flexible, H05(07) V-K	min.	0.5 mm <sup>2</sup>	max.	2.5 mm <sup>2</sup>	nominal	2.5 mm <sup>2</sup>																																																																																		
Type	flexible, H05(07) V-K																																																																																										
min.	0.5 mm <sup>2</sup>																																																																																										
max.	2.5 mm <sup>2</sup>																																																																																										
nominal	2.5 mm <sup>2</sup>																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																										
Stripping length	<table border="1"> <tr> <td>min.</td> <td>10 mm</td> </tr> <tr> <td>max.</td> <td>10 mm</td> </tr> <tr> <td>nominal</td> <td>10 mm</td> </tr> </table>	min.	10 mm	max.	10 mm	nominal	10 mm																																																																																				
min.	10 mm																																																																																										
max.	10 mm																																																																																										
nominal	10 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>0.4 Nm</td> </tr> <tr> <td>max.</td> <td>0.8 Nm</td> </tr> </table>	min.	0.4 Nm	max.	0.8 Nm																																																																																						
min.	0.4 Nm																																																																																										
max.	0.8 Nm																																																																																										

## General

Wire connection cross section AWG, max.	AWG 12	Wire connection cross section AWG, min.	AWG 30
Standards	IEC 60947-7-1	Mounting rail	TS 35

## Rating data

Rated cross-section	2.5 mm <sup>2</sup>	Rated voltage	800 V
Rated DC voltage	800 V	Nominal current	24 A
Current at maximum wires	24 A	Standards	IEC 60947-7-1
Volume resistance according to IEC 60947-7-x	1.33 mΩ	Power loss in accordance with IEC 60947-7-x	0.77 W

## UL rating data

Voltage size B (UR)	600 V	Current size B (UR)	25 A
Conductor size Factory wiring max. (UR)	12 AWG	Current size C (UR)	25 A
Voltage size C (UR)	600 V	Conductor size Factory wiring min. (UR)	30 AWG
Certificate No. (UR)	E60693	Conductor size Field wiring min. (UR)	28 AWG
Conductor size Field wiring max. (UR)	12 AWG		

**WDU 2.5 OR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Classifications**


ETIM 8.0	EC000897	ETIM 9.0	EC000897
ETIM 10.0	EC000897	ECLASS 14.0	27-25-01-01
ECLASS 15.0	27-25-01-01		

**WDU 2.5 OR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

**Drawings**

[www.weidmueller.com](http://www.weidmueller.com)



## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

Type	WQV 2.5/2	Version
Order No.	<a href="#">1053660000</a>	Cross-connector (terminal), when screwed in, yellow, 32 A, Number of
GTIN (EAN)	4008190031121	poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm
Qty.	50 ST	
Type	WQV 2.5/3	Version
Order No.	<a href="#">1053760000</a>	Cross-connector (terminal), when screwed in, yellow, 32 A, Number of
GTIN (EAN)	4008190058999	poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm
Qty.	50 ST	
Type	WQV 2.5/4	Version
Order No.	<a href="#">1053860000</a>	Cross-connector (terminal), when screwed in, yellow, 32 A, Number of
GTIN (EAN)	4008190049706	poles: 4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm
Qty.	50 ST	
Type	WQV 2.5/10	Version
Order No.	<a href="#">1054460000</a>	Cross-connector (terminal), when screwed in, yellow, 32 A, Number of
GTIN (EAN)	4008190135089	poles: 10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm
Qty.	20 ST	

## End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

## General ordering data

Type	WAP 2.5-10	Version
Order No.	<a href="#">1050000000</a>	End plate for terminals, dark beige, Height: 56 mm, Width: 1.5 mm,
GTIN (EAN)	4008190103149	V-0, Wemid, Snap-on: No
Qty.	50 ST	
Type	WAP 2.5-10 BL	Version
Order No.	<a href="#">1050080000</a>	End plate for terminals, blue, Height: 56 mm, Width: 1.5 mm, V-0,
GTIN (EAN)	4008190136611	Wemid, Snap-on: No
Qty.	50 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

Type	WAP 16+35 WTW 2.5-10	Version
Order No.	<a href="#">1050100000</a>	End and partition plate for terminals, dark beige, Height: 56 mm,
GTIN (EAN)	4008190079901	Width: 1.5 mm, V-0, Wemid
Qty.	20 ST	
Type	WAP 16+35 WTW 2.5-10 BL	Version
Order No.	<a href="#">1050180000</a>	End and partition plate for terminals, blue, Height: 56 mm, Width: 1.5
GTIN (EAN)	4008190013899	mm, V-0, Wemid
Qty.	20 ST	

## End bracket



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

## General ordering data

Type	WEW 35/2	Version
Order No.	<a href="#">1061200000</a>	End bracket, dark beige, TS 35, HB, Wemid, Width: 8 mm, 100 °C
GTIN (EAN)	4008190030230	
Qty.	50 ST	

## Testadapter and testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

## General ordering data

Type	WTA 2 WDU2.5-10	Version
Order No.	<a href="#">1632320000</a>	Test adapter (terminal), 1.5 mm <sup>2</sup> , 250 V, 6 A
GTIN (EAN)	4008190257347	
Qty.	25 ST	
Type	WTA 2/ZA WDU2.5-10	Version
Order No.	<a href="#">1632330000</a>	Test adapter (terminal), 1.5 mm <sup>2</sup> , 250 V, 6 A
GTIN (EAN)	4008190257330	
Qty.	25 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## Blank




The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet CONNECT printers. For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## General ordering data

Type	WAD 5 MC NE WS	Version
Order No.	<a href="#">1112910000</a>	Group markers, Cover, 33.3 x 5 mm, Pitch in mm (P): 5.00 WDU 2.5,
GTIN (EAN)	4032248891689	WEW 35/2, ZEW 35/2, white
Qty.	48 ST	
Type	WAD 5 MC NE GE	Version
Order No.	<a href="#">1112920000</a>	Group markers, Cover, 33.3 x 5 mm, Pitch in mm (P): 5.00 WDU 2.5,
GTIN (EAN)	4032248891771	WEW 35/2, ZEW 35/2, yellow
Qty.	48 ST	
Type	DEK 5/5 MC NE WS	Version
Order No.	<a href="#">1609801044</a>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmüller, white
Qty.	1000 ST	
Type	WS 12/5 MC NE WS	Version
Order No.	<a href="#">1609860000</a>	WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmüller,
GTIN (EAN)	4008190203481	Allen-Bradley, white
Qty.	720 ST	

## SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

## General ordering data

Type	SCHT 7	Version
Order No.	<a href="#">0517960000</a>	SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00
GTIN (EAN)	4008190001742	Weidmüller, white
Qty.	20 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

## General ordering data

Type	ZGB 15	Version
Order No.	<a href="#">1636530000</a>	Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190297053	Weidmueller, white
Qty.	20 ST	
Type	ZGB 30	Version
Order No.	<a href="#">1611930000</a>	Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190002251	Weidmueller, white
Qty.	20 ST	

## Shield clamping saddle



With our wide range of KLBÜ shield connections, you can achieve flexible and self-adjusting shield contacting and ensure error-free plant operation.

## General ordering data

Type	LS 2.8 WDU2.5-10	Version
Order No.	<a href="#">1056400000</a>	W-Series, Shield bus
GTIN (EAN)	4008190036454	
Qty.	100 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## DEK 5/5



## WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

## General ordering data

Type	DEK 5/5 MM WS	Version
Order No.	<a href="#">2007110000</a>	Dekafix, Terminal marker, 5 x 5 mm, Weidmüller, white
GTIN (EAN)	4050118391862	
Qty.	800 ST	

## End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

## General ordering data

Type	WTW EN	Version
Order No.	<a href="#">1058800000</a>	Partition plate (terminal), dark beige, Height: 86 mm, Width: 3 mm,
GTIN (EAN)	4008190140175	V-0, Wemid
Qty.	20 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

Type	WQB B/10	Version
Order No.	<a href="#">1579050000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.26 mm
GTIN (EAN)	4008190094508	
Qty.	20 ST	
Type	WQB B/2	Version
Order No.	<a href="#">1579010000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 10.14 mm
GTIN (EAN)	4008190021696	
Qty.	50 ST	
Type	WQB B/24	Version
Order No.	<a href="#">1579060000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 24, Pitch in mm (P): 5.10, Insulated: Yes, Width: 123.22 mm
GTIN (EAN)	4008190188597	
Qty.	20 ST	
Type	WQB B/3	Version
Order No.	<a href="#">1579020000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 15.28 mm
GTIN (EAN)	4008190062392	
Qty.	50 ST	
Type	WQB B/4	Version
Order No.	<a href="#">1579030000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 20.42 mm
GTIN (EAN)	4008190185046	
Qty.	50 ST	
Type	WQB B/6	Version
Order No.	<a href="#">1579040000</a>	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 30.7 mm
GTIN (EAN)	4008190081041	
Qty.	20 ST	

## Testadapter and testsockets



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## General ordering data

Type	STB 8.5/D4/2.3/M2.5 AKZ	Version
Order No.	<a href="#">0215700000</a>	Accessories, Socket
GTIN (EAN)	4008190184872	
Qty.	50 ST	

## Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

## General ordering data

Type	BZT 1 WS 10/5	Version
Order No.	<a href="#">1805490000</a>	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Type	BZT 1 ZA WS 10/5	Version
Order No.	<a href="#">1805520000</a>	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 ST	

## WS 12/5



## WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## General ordering data

Type	WS 12/5 MM WS	Version
Order No.	<a href="#">2007190000</a>	WS, Terminal marker, 12 x 5 mm, Weidmüller, white
GTIN (EAN)	4050118392036	
Qty.	800 ST	

## Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

Type	WQV 16-2.5	Version
Order No.	<a href="#">1063900000</a>	Cross-connector (terminal), when screwed in, yellow, 76 A, Number of
GTIN (EAN)	4008190112158	poles: 2, Pitch in mm (P): 11.90, Insulated: Yes, Width: 13 mm
Qty.	10 ST	

## End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

## General ordering data

Type	WAP 2.5-10/0.5MM	Version
Order No.	<a href="#">1966380000</a>	End plate for terminals, dark beige, Height: 54.5 mm, Width: 0.35
GTIN (EAN)	4032248688616	mm, V-0, Wemid, Snap-on: Yes
Qty.	50 ST	

## WDU 2.5 OR

Weidmüller Interface GmbH & Co. KG  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Accessories

## Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

## General ordering data

Type	WQV 16N-2.5	Version
Order No.	<a href="#">1073100000</a>	Cross-connector (terminal), when screwed in, yellow, 76 A, Number of
GTIN (EAN)	4008190489847	poles: 2, Pitch in mm (P): 11.90, Insulated: Yes, Width: 13 mm
Qty.	10 ST	