


WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image

More and more components need to be housed within a confined space, in switchgear and panels. As part of the power feed-in, connecting conductors is becoming increasingly challenging, especially for large cross-sections. Our comprehensive range of connection solutions also enables convenient wiring in challenging space conditions. The compact design and the combination of many practical handling benefits make the supply of power to switchgear and panels simple, efficient, and space-saving.

General ordering data

Version	Feed-through terminal block, Screw connection, dark beige, 35 mm ² , 125 A, 1000 V, Number of connections: 2
Order No.	1028800000
Type	WDU 35/ZA
GTIN (EAN)	4008190059002
Qty.	40 items

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (UR) E60693

Certificate No. (cURusEX) E184763

Dimensions and weights

Depth	62.5 mm	Depth (inches)	2.4606 inch
Depth including DIN rail	63 mm	Height	60 mm
Height (inches)	2.3622 inch	Width	16 mm
Width (inches)	0.6299 inch	Net weight	51.75 g

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-60 °C...85 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%
Product Carbon Footprint	Cradle to gate 0,376 kg CO ₂ eq.

Material data

Basic material	Wemid	Colour	dark beige
UL 94 flammability rating	V-0		

Rating data IECEx/ATEX

Certificate No. (ATEX)	DEMKO14ATEX1338U	Certificate No. (IECEx)	IECEXULD14.0005U
Max. voltage (ATEX)	690 V	Current (ATEX)	115 A
Wire cross section max. (ATEX)	35 mm ²	Max. voltage (IECEx)	690 V
Current (IECEx)	115 A	Wire cross section max. (IECEx)	35 mm ²
Marking EN 60079-7	Ex eb II C Gb	Ex 2014/34/EU label	II 2 G D

System specifications

Version	Screw connection, for screwable cross-connection, With assembly	End cover plate required	Yes
---------	---	--------------------------	-----

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

peg, One end without connector	
Number of potentials	1
Number of clamping points per level	2
Levels cross-connected internally	No
Mounting rail	TS 35
PE function	No
Number of levels	1
Number of potentials per tier	1
PE connection	No
N-function	No
PEN function	Yes

Additional technical data

Open sides	right	Number of similar terminals	1
Explosion-tested version	Yes	Type of mounting	Snap-on

CSA rating data

Voltage size C (CSA)	600 V	Current size C (CSA)	150 A
Certificate No. (CSA)	200039-1057876	Wire cross section min. (CSA)	12 AWG

Conductors for clamping (additional connection)

Connection type, additional connection Screw connection

Conductors for clamping (rated connection)

Gauge to IEC 60947-1	B8, B9
Wire connection cross section AWG, max.	AWG 2
Connection direction	on side
Tightening torque, max.	5 Nm
Tightening torque, min.	4 Nm
Stripping length	18 mm
Type of connection	Screw connection
Number of connections	2
Clamping range, max.	50 mm ²
Clamping range, min.	2.5 mm ²
Clamping screw	M 6
Blade size	6.5 x 1.2 mm
Wire connection cross section AWG, min.	AWG 12
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	35 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	2.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	35 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	2.5 mm ²
Wire connection cross section, finely stranded, max.	35 mm ²
Wire connection cross section, finely stranded, min.	2.5 mm ²
Connection cross-section, stranded, max.	50 mm ²
Connection cross-section, stranded, min.	2.5 mm ²
Twin wire-end ferrules, max.	16 mm ²
Twin wire-end ferrules, min.	1.5 mm ²

Technical data

Wire connection cross-section, solid core, max.	16 mm ²																																																																																										
Wire connection cross-section, solid core, min.	2.5 mm ²																																																																																										
Connection cross-section, finely stranded, min.	2.5 mm ²																																																																																										
Clampable conductor	<table border="1"> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>16 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table></td></tr></table>	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>16 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	solid, H05(07) V-U	min.	2.5 mm ²	max.	16 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	stranded, H07V-R	min.	2.5 mm ²	max.	50 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	flexible, H05(07) V-K	min.	2.5 mm ²	max.	35 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>solid, H05(07) V-U</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>16 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	solid, H05(07) V-U	min.	2.5 mm ²	max.	16 mm ²	nominal	35 mm ²																																																																																		
Type	solid, H05(07) V-U																																																																																										
min.	2.5 mm ²																																																																																										
max.	16 mm ²																																																																																										
nominal	35 mm ²																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table></td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	stranded, H07V-R	min.	2.5 mm ²	max.	50 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	flexible, H05(07) V-K	min.	2.5 mm ²	max.	35 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm														
Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm																																																																																				
min.	18 mm																																																																																										
max.	18 mm																																																																																										
nominal	18 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																						
min.	4 Nm																																																																																										
max.	5 Nm																																																																																										
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>stranded, H07V-R</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>50 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	stranded, H07V-R	min.	2.5 mm ²	max.	50 mm ²	nominal	35 mm ²																																																																																		
Type	stranded, H07V-R																																																																																										
min.	2.5 mm ²																																																																																										
max.	50 mm ²																																																																																										
nominal	35 mm ²																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> <tr> <td>Connection specification</td> <td>Screw connection</td> </tr> <tr> <td>Cross-section for conductor connection</td> <td> <table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table> </td> </tr> <tr> <td>wire end ferrule</td> <td> <table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table> </td></tr></table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm	Connection specification	Screw connection	Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	flexible, H05(07) V-K	min.	2.5 mm ²	max.	35 mm ²	nominal	35 mm ²	wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																												
Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm																																																																																				
min.	18 mm																																																																																										
max.	18 mm																																																																																										
nominal	18 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																						
min.	4 Nm																																																																																										
max.	5 Nm																																																																																										
Connection specification	Screw connection																																																																																										
Cross-section for conductor connection	<table border="1"> <tr> <td>Type</td> <td>flexible, H05(07) V-K</td> </tr> <tr> <td>min.</td> <td>2.5 mm²</td> </tr> <tr> <td>max.</td> <td>35 mm²</td> </tr> <tr> <td>nominal</td> <td>35 mm²</td> </tr> </table>	Type	flexible, H05(07) V-K	min.	2.5 mm ²	max.	35 mm ²	nominal	35 mm ²																																																																																		
Type	flexible, H05(07) V-K																																																																																										
min.	2.5 mm ²																																																																																										
max.	35 mm ²																																																																																										
nominal	35 mm ²																																																																																										
wire end ferrule	<table border="1"> <tr> <td>Stripping length</td> <td> <table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table> </td> </tr> <tr> <td></td> <td> <table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table> </td> </tr> </table>	Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm		<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																										
Stripping length	<table border="1"> <tr> <td>min.</td> <td>18 mm</td> </tr> <tr> <td>max.</td> <td>18 mm</td> </tr> <tr> <td>nominal</td> <td>18 mm</td> </tr> </table>	min.	18 mm	max.	18 mm	nominal	18 mm																																																																																				
min.	18 mm																																																																																										
max.	18 mm																																																																																										
nominal	18 mm																																																																																										
	<table border="1"> <tr> <td>Tightening torque</td> <td> <table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table> </td> </tr> </table>	Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																				
Tightening torque	<table border="1"> <tr> <td>min.</td> <td>4 Nm</td> </tr> <tr> <td>max.</td> <td>5 Nm</td> </tr> </table>	min.	4 Nm	max.	5 Nm																																																																																						
min.	4 Nm																																																																																										
max.	5 Nm																																																																																										

General

Wire connection cross section AWG, max.	AWG 2	Wire connection cross section AWG, min.	AWG 12
Standards	IEC 60947-7-1	Mounting rail	TS 35

Rating data

Rated cross-section	35 mm ²	Rated voltage	1000 V
Rated DC voltage	1000 V	Nominal current	125 A
Current at maximum wires	150 A	Standards	IEC 60947-7-1
Volume resistance according to IEC 60947-7-x	0.26 mΩ	Rated impulse withstand voltage	8 kV
Power loss in accordance with IEC 60947-7-x	4.00 W	Pollution severity	3

UL rating data

Conductor size Factory wiring max. (UR) 0 AWG	Current size C (UR)	150 A
Voltage size C (UR)	Conductor size Factory wiring min. (UR)	12 AWG
Certificate No. (UR)	Conductor size Field wiring min. (UR)	12 AWG
Conductor size Field wiring max. (UR)		

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Classifications**


ETIM 8.0	EC000897	ETIM 9.0	EC000897
ETIM 10.0	EC000897	ECLASS 14.0	27-25-01-01
ECLASS 15.0	27-25-01-01		

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany


Drawings

www.weidmueller.com



Accessories

Cross connector



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Type	WQV 35/2	Version
Order No.	1053060000	Cross-connector (terminal), when screwed in, yellow, 138 A, Number
GTIN (EAN)	4008190097349	of poles: 2, Pitch in mm (P): 16.00, Insulated: Yes, Width: 9.85 mm
Qty.	50 ST	
Type	WQV 35/3	Version
Order No.	1055360000	Cross-connector (terminal), when screwed in, yellow, 112 A, Number
GTIN (EAN)	4008190007249	of poles: 3, Pitch in mm (P): 16.00, Insulated: Yes, Width: 9.85 mm
Qty.	50 ST	
Type	WQV 35/4	Version
Order No.	1055460000	Cross-connector (terminal), when screwed in, yellow, 112 A, Number
GTIN (EAN)	4008190130275	of poles: 4, Pitch in mm (P): 16.00, Insulated: Yes, Width: 9.85 mm
Qty.	50 ST	
Type	WQV 35/10	Version
Order No.	1053160000	Cross-connector (terminal), when screwed in, yellow, 112 A, Number
GTIN (EAN)	4008190026028	of poles: 10, Pitch in mm (P): 16.00, Insulated: Yes, Width: 9.85 mm
Qty.	10 ST	

End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

General ordering data

Type	WAP 16+35 WTW 2.5-10	Version
Order No.	1050100000	End and partition plate for terminals, dark beige, Height: 56 mm,
GTIN (EAN)	4008190079901	Width: 1.5 mm, V-0, Wemid
Qty.	20 ST	
Type	WAP 16+35 WTW 2.5-10 BL	Version
Order No.	1050180000	End and partition plate for terminals, blue, Height: 56 mm, Width: 1.5
GTIN (EAN)	4008190013899	mm, V-0, Wemid
Qty.	20 ST	

Accessories

End bracket



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Type	WEW 35/1	Version
Order No.	1059000000	End bracket, dark beige, TS 35, V-2, Wemid, Width: 12 mm, 100 °C
GTIN (EAN)	4008190172282	
Qty.	50 ST	

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	DEK 5/5 MC NE WS	Version
Order No.	1609801044	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1000 ST	
Type	WS 12/5 MC NE WS	Version
Order No.	1609860000	WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190203481	Allen-Bradley, white
Qty.	720 ST	

Accessories

SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw.

The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

Type	SCHT 7	Version
Order No.	0517960000	SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00
GTIN (EAN)	4008190001742	Weidmueller, white
Qty.	20 ST	

ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

Type	ZGB 15	Version
Order No.	1636530000	Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190297053	Weidmueller, white
Qty.	20 ST	
Type	ZGB 30	Version
Order No.	1611930000	Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190002251	Weidmueller, white
Qty.	20 ST	

Accessories

End plates and partition plates



Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

General ordering data

Type	WTW EN	Version
Order No.	1058800000	Partition plate (terminal), dark beige, Height: 86 mm, Width: 3 mm,
GTIN (EAN)	4008190140175	V-0, Wemid
Qty.	20 ST	

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snapped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Type	BZT 1 WS 10/5	Version
Order No.	1805490000	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Type	BZT 1 ZA WS 10/5	Version
Order No.	1805520000	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 ST	

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Accessories

WS 12/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.


Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

Type	WS 12/5 MM WS	Version
Order No.	2007190000	WS, Terminal marker, 12 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392036	
Qty.	800 ST	

With lightning flash



The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet CONNECT printers. For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	WAD 12 MC B GE/SW	Version
Order No.	2445090000	Group markers, Cover, 36.2 x 11.9 mm, WDU 16, WDU 35, yellow
GTIN (EAN)	4050118457896	
Qty.	32 ST	

WDU 35/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Accessories

Blank




The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet CONNECT printers. For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	WAD 12 MC NE WS	Version
Order No.	2445070000	Group markers, Cover, 36.2 x 11.9 mm, WDU 16, WDU 35, white
GTIN (EAN)	4050118458220	
Qty.	32 ST	
Type	WAD 12 MC NE GE	Version
Order No.	2445080000	Group markers, Cover, 36.2 x 11.9 mm, WDU 16, WDU 35, yellow
GTIN (EAN)	4050118458213	
Qty.	32 ST	

Cross connector



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Type	WQV 35-4/6	Version
Order No.	1064200000	Cross-connector (terminal), when screwed in, yellow, 41 A, Number of poles: 2, Pitch in mm (P): 16.00, Insulated: Yes, Width: 13 mm
GTIN (EAN)	4008190072919	
Qty.	10 ST	
Type	WQB-PEN 35	Version
Order No.	1060100000	Cross-connector (terminal), when screwed in, Silver grey, 135 A, Number of poles: 2, Pitch in mm (P): 16.00, Insulated: No, Width: 24.6 mm
GTIN (EAN)	4008190089870	
Qty.	10 ST	