

**WAP 2.5-10 GR****Weidmüller Interface GmbH & Co. KG**Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

**Product image**

Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

**General ordering data**

|            |  |
|------------|--|
| Version    | End plate for terminals, grey, Height: 56 mm, Width: 1.5 mm, V-0, Wemid, Snap-on: No |
| Order No.  | <a href="#">1050050000</a>   |
| Type       | WAP 2.5-10 GR  |
| GTIN (EAN) | 4008 190455484   |
| Qty.       | 50 items   |

## WAP 2.5-10 GR

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Dimensions and weights

|            |         |                 |             |
|------------|---------|-----------------|-------------|
| Depth      | 33.5 mm | Depth (inches)  | 1.3189 inch |
| Height     | 56 mm   | Height (inches) | 2.2047 inch |
| Width      | 1.5 mm  | Width (inches)  | 0.0591 inch |
| Net weight | 2.58 g  |                 |             |

### Temperatures

|                                  |                |                                  |                |
|----------------------------------|----------------|----------------------------------|----------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -60 °C...85 °C |
| Continuous operating temp., min. | -60 °C         | Continuous operating temp., max. | 130 °C         |

### Environmental Product Compliance

|                          |                             |                  |  |
|--------------------------|-----------------------------|------------------|--|
| RoHS Compliance Status   | Compliant without exemption |                  |  |
| REACH SVHC               | No SVHC above 0.1 wt%       |                  |  |
| Product Carbon Footprint | Cradle to gate              | 0,023 kg CO2 eq. |  |

### Material data

|                           |       |        |      |
|---------------------------|-------|--------|------|
| Basic material            | Wemid | Colour | grey |
| UL 94 flammability rating | V-0   |        |      |

### System specifications

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

### Additional technical data

|         |    |                     |                 |
|---------|----|---------------------|-----------------|
| Snap-on | No | Installation advice | Direct mounting |
|---------|----|---------------------|-----------------|

### Dimensions

|              |       |
|--------------|-------|
| TS 35 offset | 66 mm |
|--------------|-------|

### General

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC000886    | ETIM 9.0    | EC000886    |
| ETIM 10.0   | EC000886    | ECLASS 14.0 | 27-25-03-01 |
| ECLASS 15.0 | 27-25-03-01 |             |             |