

Product image

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Connecting sleeve (terminal), when screwed in, Width: 4 mm, Height: 4 mm, Depth: 12.2 mm, Number of poles: 1, Cu Zn
Order No.	1056500000
Type	VH 12.4/4/2.8
GTIN (EAN)	4008190162771
Qty.	50 items

VH 12.4/4/2.8

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

RoHS	Conform
------	---------

Dimensions and weights

Depth	12.2 mm	Depth (inches)	0.4803 inch
Height	4 mm	Height (inches)	0.1575 inch
Width	4 mm	Width (inches)	0.1575 inch
Diameter	4 mm	Net weight	0.68 g

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
---------------------	----------------	---------------------	---------------

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Basic material	Cu Zn	Colour	Silver grey
----------------	-------	--------	-------------

System specifications

Version	for cross-connection link
---------	---------------------------

Additional technical data

Type of fixing	when screwed in
----------------	-----------------

Dimensions

Diameter	4 mm
----------	------

General

Number of poles	1
-----------------	---

Classifications

ETIM 8.0	EC002848	ETIM 9.0	EC002848
ETIM 10.0	EC002848	ECLASS 14.0	27-25-03-90
ECLASS 15.0	27-25-03-90		