

Product image

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

| | |
|------------|---|
| Version | Connecting sleeve (terminal), when screwed in, Width: 4 mm, Height: 4 mm, Depth: 12.2 mm, Number of poles: 1, Cu Zn |
| Order No. | 1056500000 |
| Type | VH 12.4/4/2.8 |
| GTIN (EAN) | 4008190162771 |
| Qty. | 50 items |

Technical data

Approvals

ROHS Conform

Dimensions and weights

| | | | |
|----------|---------|-----------------|-------------|
| Depth | 12.2 mm | Depth (inches) | 0.4803 inch |
| Height | 4 mm | Height (inches) | 0.1575 inch |
| Width | 4 mm | Width (inches) | 0.1575 inch |
| Diameter | 4 mm | Net weight | 0.68 g |

Temperatures

Storage temperature -25 °C...55 °C Ambient temperature -5 °C...40 °C

Environmental Product Compliance

RoHS Compliance Status Compliant without exemption
 REACH SVHC No SVHC above 0.1 wt%

Material data

Basic material Cu Zn Colour Silver grey

System specifications

Version for cross-connection link

Additional technical data

Type of fixing when screwed in

Dimensions

Diameter 4 mm

General

Number of poles 1

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002848 | ETIM 9.0 | EC002848 |
| ETIM 10.0 | EC002848 | ECLASS 14.0 | 27-25-03-90 |
| ECLASS 15.0 | 27-25-03-90 | | |