

## IE-BID-24V

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



PushPull Power plug-in connector according to PROFINET specification

### General ordering data

Version	Insert, PROFINET, Socket connector
Order No.	<a href="#">1068940000</a>
Type	IE-BID-24V
GTIN (EAN)	4032248823086
Qty.	100 items

## IE-BID-24V

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Approvals

ROHS Conform

## Dimensions and weights

Height	13.5 mm	Height (inches)	0.5315 inch
Width	27.4 mm	Width (inches)	1.0787 inch
Length	13.1 mm	Length (inches)	0.5157 inch
Net weight	2.6 g		

## Temperatures

Storage temperature	Operating temperature	-40 °C...70 °C
Installation temperature		

## Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

## General data

Number of poles	5	Contact surface	Gold over nickel
Shielding	unshielded	Colour	black
Contact material	Copper alloy	Plugging cycles	≤ 100
Connection 1	PushPull Power	Connection 2	Dip soldering

## Electrical properties

Operating voltage	24 V	Current-carrying capacity at 50 °C	16 A
-------------------	------	------------------------------------	------

## General standards

Connector standard	IEC 61076-3-126
--------------------	-----------------

## Standards

Connector standard	IEC 61076-3-126
--------------------	-----------------

## Classifications

ETIM 8.0	EC001121	ETIM 9.0	EC001121
ETIM 10.0	EC001121	ECLASS 14.0	27-44-03-90
ECLASS 15.0	27-44-03-90		


**IE-BID-24V**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

**Drawings**

[www.weidmueller.com](http://www.weidmueller.com)

**Dimensioned drawing**



**Detailed drawing**

Stiftquerschnitt/  
pin cross-section

