

Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The RockStar® HighPower housings are manufactured from high-strength die-cast aluminium and offer perfect protection against harsh environmental conditions thanks to continual optimisation. The multi-part housing gives users the opportunity to examine work processes down to the last step in the workflow.

### **General ordering data**

Version	HDC enclosures, Installation size: 8, Protection degree: IP68, IP69, in plugged condition, Plug housing, Clamping yoke connection, Standard
Order No.	<u>1079930000</u>
Туре	HDC IP68 HP 24B TO
GTIN (EAN)	4032248842032
Qty.	1 items





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Approvals			
ROHS	Conform		
Dimensions and weights			
Depth	192 mm	Depth (inches)	7.559 inch
Height	120 mm	Height (inches)	4.7244 inch
Width	64 mm	Width (inches)	2.5197 inch
Net weight	822.72 g		2.3137 111011
Temperatures			
Limit temperature	-50 °C 120 °C		
Environmental Product C	Compliance		'
RoHS Compliance Status	Compliant without exemp	tion	
REACH SVHC	No SVHC above 0.1 wt%		
Chemical resistance	Substance	Aceto	one
	Chemical resistance		tant
	Substance Diesel oil		el oil
	Chemical resistance U		able
	Substance	Ethyl	alcohol
	Chemical resistance	Resis	tant
	Substance	Trans	smission oil
	Chemical resistance	Cond	itionally resistant
	Substance	Hydra	aulic oil
	Chemical resistance	Cond	itionally resistant
	Substance	Petro	leum benzine
	Chemical resistance	Unsta	able
	Substance	Swea	
	Chemical resistance		itionally resistant
	Substance	Prem	ium gasoline
	Chemical resistance	Unsta	able
	Substance	Wate	r
	Chemical resistance	Resis	tant
	Substance	UV	
	Chemical resistance	Resis	tant
	Substance	Ozon	e
		Resis	

#### **General data**

Design of housing	Plug housing	Installation size	8
Colour	black, black (similar to RAL 9005)	Surface finish	Powder coating
Туре	Plug	Series	HighPower
Free from halogens	false	BG	8
Protection degree	IP68, IP69, in plugged condition		

### **General data**

Tightening torque	11 Nm	Housing main material	diecast aluminium
Surface finish	Powder coating	Protection degree	IP68, IP69, in plugged
			condition

Catalogue status / Drawings 2





### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Series	HighPower	EMC housings	Yes
Material of locking element	Stainless steel, rust-proof		
Version			
Top part/bottom part/lid	upper part	Tightening torque	11 Nm
Design of housing	Plug housing	Design of locking system	Clamping yoke connection
Design	Standard	Installation size	8
Type	Plug	Clamp version	Clamping yoke connection
Colour (RAL)	RAL 9011, RAL 9005	BG	8
Important note			
Important note Product information	voltage and contain corres	d operation, internally generated volta ponding peaks. It is imperative to ens ge. For applications outside of this sp	sure that these peak voltages do
	voltage and contain corres	ponding peaks. It is imperative to ens	sure that these peak voltages do
Product information	voltage and contain corres	ponding peaks. It is imperative to ens	sure that these peak voltages do
Product information  Classifications	voltage and contain corres not exceed the rated voltag	ponding peaks. It is imperative to ens ge. For applications outside of this sp	sure that these peak voltages do ecification, please contact us.
Product information  Classifications  ETIM 6.0	voltage and contain corres not exceed the rated voltage EC000437	ponding peaks. It is imperative to ens ge. For applications outside of this sp ETIM 7.0	sure that these peak voltages do ecification, please contact us.  EC000437
Product information  Classifications  ETIM 6.0  ETIM 8.0	voltage and contain corres not exceed the rated voltage EC000437 EC000437	ponding peaks. It is imperative to ensige. For applications outside of this sp  ETIM 7.0  ETIM 9.0	EC000437
Product information  Classifications  ETIM 6.0  ETIM 8.0  ETIM 10.0	voltage and contain corres not exceed the rated voltage EC000437 EC000437 EC000437	ponding peaks. It is imperative to ensige. For applications outside of this sp  ETIM 7.0  ETIM 9.0  ECLASS 9.0	EC000437 EC000437 27-44-02-02
Product information  Classifications  ETIM 6.0  ETIM 8.0  ETIM 10.0  ECLASS 9.1	EC000437 EC000437 EC000437 27-44-02-02	ponding peaks. It is imperative to enspe. For applications outside of this specific productions outside of this specific productions.  ETIM 7.0  ETIM 9.0  ECLASS 9.0  ECLASS 10.0	EC000437 EC000437 27-44-02-02 27-44-02-02

Catalogue status / Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Drawings**





To avoid damage to the contacts and insulating sleeves, we recommend fixing the cable. The corresponding distances are shown in the following drawing. The cable fixation is not included in the scope of delivery.

**Data sheet** 





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

**Drawings** 



Weidmüller Interface GmbH & Co. KG

6

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### Socket wrench sets



Allen key made from fully hardened, high-alloy chromium-vanadium- steel, acc. to DIN ISO 2936 L (DIN 911), high-quality refined surface.

### **General ordering data**

Туре	SK WSD-S 1,5-10,0	Version
Order No.	9008850000	Mounting tool
GTIN (EAN)	4032248266609	
Qty.	1 ST	

### **HighPower spare parts**



### **General ordering data**

Туре	HDC HP TO SCREW SET	Version
Order No.	2447770000	HDC-HighPower
GTIN (EAN)	4050118461688	
Qty.	10 ST	
Туре	HDC HP TO SCREW SET	Version
Type Order No.	HDC HP TO SCREW SET 2447770000	Version HDC-HighPower

Catalogue status / Drawings