

HDC HP 250 SHOCKPROTEC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The RockStar® HighPower housings are manufactured from high-strength die-cast aluminium and offer perfect protection against harsh environmental conditions thanks to continual optimisation. The multi-part housing gives users the opportunity to examine work processes down to the last step in the workflow.

General ordering data

| | |
|------------|---|
| Version | Accessories, Screw connection, Installation size: 250 |
| Order No. | 1120130000 |
| Type | HDC HP 250 SHOCKPROTEC |
| GTIN (EAN) | 4032248901487 |
| Qty. | 1 items |

HDC HP 250 SHOCKPROTEC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|----------|---------|-----------------|-------------|
| Length | 37 mm | Length (inches) | 1.4567 inch |
| Diameter | 12.3 mm | Net weight | 2 g |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

General data

| | | | |
|---------------------------|------------------|---------------------|--|
| Type of connection | Screw connection | Installation size | 250 |
| UL 94 flammability rating | V-0 | Colour | black |
| Insulation resistance | 1010 Ω | Insulating material | Polyamide with fibre optic |
| Pollution severity | PD 2 (PD 3) | Basic material | PA 66 GF 30, Stainless steel, rust-proof |
| Series | HighPower | Free from halogens | false |
| BG | 250 | | |

General data

| | | | |
|--------------------|--|--------|-----------|
| Type of connection | Screw connection | Colour | black |
| Basic material | PA 66 GF 30, Stainless steel, rust-proof | Series | HighPower |

Important note

| | |
|---------------------|---|
| Product information | Depending on the intended operation, internally generated voltages can superimpose the working voltage and contain corresponding peaks. It is imperative to ensure that these peak voltages do not exceed the rated voltage. For applications outside of this specification, please contact us. |
|---------------------|---|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002943 | ETIM 9.0 | EC002943 |
| ETIM 10.0 | EC002943 | ECLASS 14.0 | 27-44-02-92 |
| ECLASS 15.0 | 27-44-02-92 | | |

HDC HP 250 SHOCKPROTEC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings

www.weidmueller.com

