

**SAI-M23-SE-19****Weidmüller Interface GmbH & Co. KG**Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com



The M23 round plug-in connectors offer a high number of mating cycles, high current-carrying capacity and high contact-density coupled with minimum dimensions. Enclosures, inserts and crimp contacts need to be ordered separately.

**General ordering data**

Version	Sensor/Actuator plug-in connector, Insert
Order No.	<a href="#">1170120000</a>
Type	SAI-M23-SE-19
GTIN (EAN)	4032248962068
Qty.	1 items

## Technical data

## Approvals

Approvals



ROHS	Conform
UL File Number Search	<a href="#">UL Website</a>
Certificate No. (UR)	E344862

## Dimensions and weights

Net weight	3 g
------------	-----

## Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

## Technical data customisable plug-in connectors


Number of poles	19	Coding	none
Type of connection	Crimp connection	Housing main material	Thermoplastic polyamide PA 6, PBT
Nominal voltage	100 V	Plugging cycles	> 1000
Pollution severity	3	Rated current	1 mm contact = 8 A, 1.5 mm contact = 10 A
Gender of contact	Male	Coding possibilities for M23 signal inserts	H-coded, N-coded, S-coded, X-coded, Y-coded

## Classifications


ETIM 8.0	EC003557	ETIM 9.0	EC003557
ETIM 10.0	EC003557	ECLASS 14.0	27-44-02-23
ECLASS 15.0	27-44-02-23		

**Drawings**

**Pinning**



**Dimensioned drawing**



**Technical data**

Number of positions	6	7	9	12	16	17	19			
Number of contacts	6	7	8	1	12	16	17	16	3	
Contact-ø	mm	2	2	1	2	1	1	1	1	1.5

