

## AIE MULTI-STRIPAX PV

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)



- For flexible and solid conductors with special insulating materials
- High-quality stripping for industrial applications (complies with aircraft industry requirements)
- Specially shaped blades enable stripping of special types of insulation and conductor configurations
- Stripping length adjustable via end stop
- Very versatile thanks to interchangeable stripping units
- Stripping results reproduced accurately over and over again
- No damage to the conductor
- A long-lasting, reliable tool thanks to its sturdy design
- Integrated cutting function

### General ordering data

Version	Insert
Order No.	<a href="#">1204280000</a>
Type	AIE MULTI-STRIPAX PV
GTIN (EAN)	4032248987030
Qty.	1 items

## AIE MULTI-STRIPAX PV

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Depth	30 mm	Depth (inches)	1.1811 inch
Height	3 mm	Height (inches)	0.1181 inch
Width	41 mm	Width (inches)	1.6142 inch
Length	41 mm	Length (inches)	1.6142 inch
Net weight	66 g		

### Environmental Product Compliance

RoHS Compliance Status	Not affected
REACH SVHC	Lead 7439-92-1
SCIP	cf06c250-ed1e-4a45-9c1b-c5c8cbf13bf0

### Technical data

Description of article	Stripping mechanism for photovoltaic cables and similar earthing cables and short-circuit-proof cables: 2.5 to 6 mm <sup>2</sup> , Stripping mechanism for photovoltaic cables and similar earthing cables and short-circuit-proof cables: 4 to 10 mm <sup>2</sup>
------------------------	---

### Stripping tools

Stripping length, min.	2 mm	Conductor cross-section, max.	10 mm <sup>2</sup>
Conductor cross-section, min.	4 mm <sup>2</sup>	Workable cable	PV cable

### Classifications

ETIM 8.0	EC001509	ETIM 9.0	EC001509
ETIM 10.0	EC001509	ECLASS 14.0	21-04-48-91
ECLASS 15.0	21-04-48-91		