#### Q 2 DLI



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

### **Product image**









The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

#### **General ordering data**

Cross-connector (terminal), when screwed in, grey, 24 A, Number of poles: 2, Pitch in mm (P): 6.10, Insulated: No, Width: 11.1 mm
<u>1312500000</u>
Q 2 DLI
4008190039837
50 items



## Q 2 DLI



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Conform		
0	D (1 (' 1 )	0.045 : 1
		0.315 inch
		0.1575 inch
	vviatn (inches)	0.437 inch
1.4 g		
-25 °C55 °C	Ambient temperature	-5 °C40 °C
ompliance		
Compliant without even	antion	
140 04110 45040 0.1 4417		
CuSn	Colour	grey
for cross-connection linl	<	
1		
		Di di
	Installation advice	Direct mounting
No		
6.10 mm		
6.10 mm		
6.10 mm 2	Installation advice	Direct mounting
	Installation advice	Direct mounting
	Installation advice	Direct mounting
2	Installation advice	Direct mounting
2 24 A		
2	Installation advice  ETIM 9.0 ECLASS 14.0	Direct mounting  EC000489 27-25-03-03
	8 mm 4 mm 11.1 mm 1.4 g  -25 °C55 °C  compliance  Compliant without exen No SVHC above 0.1 wto	8 mm

Catalogue status / Drawings 2