


VSSC6TRSL24VAC/DC0.5A

Weidmüller Interface GmbH & Co. KG

Klingenbergsstraße 26
D-32758 Detmold
Germanywww.weidmueller.com

Similar to illustration

Overvoltage coupling along the conductor path may disturb or destroy sensitive signal inputs. It is important to provide protection in the immediate vicinity of I&C devices. Weidmüller's broad product range for the I&C sector offers products in a 2-piece, pluggable design and modular terminals for tension clamp or screw connection. These products are suitable for both binary and analogue signals. Weidmüller also offers other designs with integrated components such as gas discharge tubes or varistors. VARITECTOR stands for flexible and variable surge protection by Weidmüller, tested according to product standard IEC61643-21. The VARITECTOR series can be used in applications according to IEC 61643-22 / VDE 0845-3 for classes C1, C2, C3 and D1. The VARITECTOR SPC, SSC and MCZ OVP product families optimally combine electrical and mechanical properties. Size and easy handling play an important role. This surge protection is suited for confined spaces in industrial and process automation as well as in building automation applications.



General ordering data

Version	Surge protection for instrumentation and control, Surge protection for measurement and control, UP(L/N-PE) 150 V
Order No.	1354790000
Type	VSSC6TRSL24VAC/DC0.5A
GTIN (EAN)	4050118156744
Qty.	10 items

VSSC6TRSL24VAC/DC0.5A

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



CSAEX



ROHS

Conform

UL File Number Search

[UL Website](#)

Certificate No. (UL)

E311081

Dimensions and weights

Depth	81 mm
Height	88.5 mm
Width	6.2 mm
Net weight	47 g

Depth (inches)	3.189 inch
Height (inches)	3.4842 inch
Width (inches)	0.2441 inch

Temperatures

Storage temperature	-40 °C...80 °C
Humidity	5...96 %

Operating temperature	-40 °C...70
-----------------------	-------------

Probability of failure

SIL in compliance with IEC 61508	3
SFF	96.67 %
PFH in 1*10-9 per hour	1.8

MTTF	1358 a
λges	54

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	71e97bb7-979f-4330-94c0-20c629bb05e3

Rated data UL

Certificate No. (UL)	E311081	UL certificate	UL Zertifikat - PDF/ E311081VOL1SEC3.pdf (application/pdf)
----------------------	---------	----------------	--

CSA protection data

Gas group D	IIA
Input-current, max. II	500 mA
Internal inductance, max. LI	0 µH
Input voltage, max. Ui	42 V

Gas groups A, B	IIC
Gas group C	IIB
Internal capacity, max. CI	2 nF

General data

Optical function display	No	Segment	Measurement - Monitoring - Setting
Version	Surge protection for measurement and control	Design	Terminal
UL 94 flammability rating	V-0	Colour	black
Protection degree	IP20	Mounting rail	TS 35

VSSC6TRSL24VAC/DC0.5A

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Isolating function	Yes	Operating altitude	≤ 2000 m
Testing option	Functional screw with test plug receptacle, connections 1, 2, 4, 5		

Insulation coordination acc. to EN 50178

Surge voltage category	III	Pollution severity	2
------------------------	-----	--------------------	---

Rated data IEC / EN

Number of poles	1	Leakage current at Un	2.8 mA
Rated voltage (AC)	24 V	Rated voltage (DC)	34 V
Rated current IN	500 mA	Protection level UP (typ.)	150 V
Voltage type	AC/DC	Fuse protection	0.5 A
Volume resistance	1.8 Ω 10 %	Standards	IEC 61643-21
Lightning test current limp (10/350 µs)	1 kA	Discharge current, max. (8/20 µs)	20 kA
Requirements category acc. to IEC 61643-21	C2, C3, D1	Insertion loss	3.12 Mhz
Max. continuous voltage, Uc (AC)	30 V	Max. continuous voltage, Uc (DC)	42 V
Surge current-carrying capacity D1	1 kA 10/350 µs	Surge current-carrying capacity C3	10 A 10/1000 µs
Pulse-reset capacity	≤ 20 ms	Signal transmission properties (-3 dB)	3.2 MHz
Lightning test current, limp (10/350 µs)	1 kA	Overload - failure mode	Modus 2
Wire-PE		Discharge current In (8/20µs) wire-PE	2.5 kA
Protection level UP for C1 with 500V/250A (wire-wire)	116 V	Protection level UP for C3 with 1kV/µs (wire-wire)	106 V
Discharge current Imax (8/20µs) wire-PE10 kA		Protection level UP for C3 with 1kV/µs (wire-PE)	55 V
Protection level UP for D1 with 0.5kA	194 V	Surge current-carrying capacity C2	2.5 kA 8/20 µs 5 kV 1.2/50 µs
Protection level UP for C2 with 10kV/5kA (wire-wire)	204 V	Protection level UP for C2 with 10kV/5kA (wire-PE)	108 V
Protection level UP for C1 with 500V/250A (wire-PE)	60 V		

Further details of approvals

GOST certificate	GOST-Zertifikat - PDF/7950_n1-n4.pdf (application/pdf)
------------------	--

Connection data

Type of connection	Screw connection	Tightening torque, min.	0.5 Nm
Tightening torque, max.	0.8 Nm	Clamping range, min.	0.5 mm ²
Clamping range, max.	4 mm ²	Wire cross-section, solid, min.	0.5 mm ²
Wire cross-section, solid, max.	6 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	4 mm ²	Connection cross-section, stranded, min.	0.5 mm ²
Connection cross-section, stranded, max.	4 mm ²		

Electrical data

Voltage type	AC/DC
--------------	-------

VSSC6TRSL24VAC/DC0.5A

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

General data

Number of poles	1	Protection degree	IP20
Colour	black		

Ratings IECEx/ATEX/cUL

cUL certificate	cUL Certificate - pdf/ VSSC.PDF (application/ pdf)
-----------------	--

Important note

Product information	Mode 2: State where the voltage-limiting part of the SPD was short-circuited due to a very low impedance within the SPD. The line is inoperable, but the measuring equipment is still protected by means of a short-circuit.
---------------------	--

Classifications

ETIM 8.0	EC000943	ETIM 9.0	EC000943
ETIM 10.0	EC000943	ECLASS 14.0	27-17-15-01
ECLASS 15.0	27-17-15-01		

Tender specification sheets

Long specification	Surge protection in a one piece, 6.2 mm wide DIN rail module for two binary, potential-free signal circuits with 24 V UC. Each signal path can be opened using an isolator. Signal indication via a green LED. When the terminal is fitted, a simultaneous electrically conducting contact is made between the mounting rail (earth) and the reference potential (ground) of the protection circuit in the terminal. Optical identification of the terminal based on the type of protected switching and the voltage level. The terminal can be labelled or marked.	Short specification	Surge protection in a one piece, 6.2 mm wide DIN rail module for two binary, potential-free signal circuits. Each signal path can be opened using an isolator. Signal indication via a green LED. Version: 24V UC
--------------------	---	---------------------	---

VSSC6TRSL24VAC/DC0.5A

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Similar to illustration

Circuit diagram

