

SAIE-M12B-5S-TL-HW-PG9**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

Various build-in connectors are required for the connections on the device side of the sensor/actuator cabling. These are available in the versions M12, M8 and M5.

General ordering data

| | |
|------------|--|
| Version | Built-in plugs, M12, Mounting thread: , Number of poles: 5, Strand / cable length: |
| Order No. | 1467780000 |
| Type | SAIE-M12B-5S-TL-HW-PG9 |
| GTIN (EAN) | 4050118273649 |
| Qty. | 20 items |

SAIE-M12B-5S-TL-HW-PG9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

ROHS Conform

Dimensions and weights

Net weight 15.73 g

Environmental Product Compliance

RoHS Compliance Status Compliant with exemption

RoHS Exemption (if applicable/known) 6c

REACH SVHC Lead 7439-92-1

SCIP bd63baef-8092-4596-90c7-5b4daa22710b

Technical specifications for cable

Number of poles 5

Technical data customisable plug-in connectors

| | | | |
|------------------------------|----------------|--------------------|--|
| Number of poles | 5 | Coding | A-coded |
| Contact surface | Gold-plated | Type of connection | Socket connector |
| Housing main material | Zinc diecast | Nominal voltage | 125 V |
| Nominal current | 4 A | Protection degree | IP67, when fully mounted |
| Cable gland | PG 9 | Rated current | 4 A (4- and 5-pole)/ 2 A (8-pole)/ 1.5 A (12-pole) |
| Temperature range of housing | -40 ... +85 °C | | |

Standards

Connector standard IEC 61076-2-101

General data

| | | | |
|------------------------------|---|-----------------------|--|
| Number of poles | 5 | Coding | A-coded |
| Connection thread | M12 | Contact surface | Gold-plated |
| Type of connection | Socket connector | Housing main material | Zinc diecast |
| Nominal voltage | 125 V | Nominal current | 4 A |
| Protection degree | IP67, when fully mounted | Cable gland | PG 9 |
| Rated voltage | 250 V (4-pole)/ 60 V (5-pole)/ 30 V (8 and 12-pole) | Rated current | 4 A (4- and 5-pole)/ 2 A (8-pole)/ 1.5 A (12-pole) |
| Connection 1 | M12 | Connection 2 | Dip soldering |
| Temperature range of housing | -40 ... +85 °C | Conductor O.D. | - |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC003568 | ETIM 9.0 | EC003568 |
| ETIM 10.0 | EC003568 | ECLASS 14.0 | 27-44-01-10 |
| ECLASS 15.0 | 27-44-01-10 | | |

Pole scheme

