



The use of insulated connectors guarantees users consistent electrical connection quality in the long term.

- Wide range of insulated and non-insulated cable lugs and connectors
- Tubular cable lugs according to current market standards (Euroseries)
- Compression cable lugs acc. to DIN 46235
- Sheet metal cable lugs acc. to DIN 46234
- Insulated ring cable lugs to DIN 46237
- Insulated pin cable lugs to DIN 46231

**General ordering data**

Version	cable lug, terminal end, 16 mm <sup>2</sup>
Order No.	<a href="#">1494100000</a>
Type	KQN-M10/-16
GTIN (EAN)	4050118303728
Qty.	100 items

**Technical data****Approvals**

ROHS	Conform
------	---------

**Dimensions and weights**

Net weight	5 g
------------	-----

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Connectors**

Conductor cross-section	16 mm <sup>2</sup>	Insulation	not available
Hole	M10	Inside diameter of shaft (d1)	5.8 mm
Outside diameter of shaft (d3)	18 mm	Shaft length (a)	10 mm
Connection length (l)	24 mm	Inside diameter of flange (d2)	10.5 mm

**Classifications**

ETIM 8.0	EC001059	ETIM 9.0	EC001059
ETIM 10.0	EC001059	ECLASS 14.0	27-40-02-12
ECLASS 15.0	27-40-02-12		

**Drawings**

