# HSS 1.0-3.2 EL Y30M

The heat-shrinkable sleeve is printable on 2 sides and can be used for marking and insulating cables and wires. The flexible, heat-shrink material enables a firm, perfect fit around the conductor and therefore saves space.

## General ordering data

| | |
|---|---|
| Version | Conductor and cable markers, 1 - 3.2 mm, yellow |
| Order No. | 1505770000 |
| Type | HSS 1.0-3.2 EL Y30M |
| GTIN (EAN) | 4050118314328 |
| Qty. | 1 items |

Creation date 27.02.2026 11:34:46 MEZ

## HSS 1.0-3.2 EL Y30M

## Technical data

### Approvals

| | |
|---|---|
| Approvals | |
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate No. (cURus) | E366310 |

### Dimensions and weights

| | | | |
|---|---|---|---|
| Depth | 0.77 mm | Depth (inches) | 0.0303 inch |
| Width | 5.6 mm | Width (inches) | 0.2205 inch |
| Length | 30000 mm | Length (inches) | 1181.1 inch |
| Net weight | 172 g | | |

### Temperatures

| | |
|---|---|
| Operating temperature range | -55...135 °C |

### Environmental Product Compliance

| | |
|---|---|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

### General data

| | | | |
|---|---|---|---|
| Type of printing | neutral | Width | 5.6 mm |
| Operating temperature range, max. | 135 °C | Operating temperature range, min. | -55 °C |
| Colour | yellow | Halogen | Yes |
| Length | 30000 mm | Basic material | Polyolefine |
| Printed characters | without | Recommended industries | Plant manufacture, Energy, Device manufacturer, Machinery |
| compatible printer | THM MULTIMARK, THM MULTIMARK PLUS | Operating temperature range | -55...135 °C |
| Number per roll | 1 | | |

### Conductor and cable markers

| | | | |
|---|---|---|---|
| Halogen | Yes | Conductor cross-section, max. | 1.5 mm² |
| Conductor cross-section, min. | 0.5 mm² | Conductor O.D., max. | 3.2 mm |
| Conductor O.D., min. | 1 mm | Rate of shrinkage | 3:1 |
| Recommended shrinking temperature | 90 °C | Text field width | 0 mm |
| Text field height | 5.4 mm | Conductor O.D. | 1 - 3.2 mm |
| Cross-section for connected wire | 0.5 - 1.5 mm² | | |

### Important note

| | |
|---|---|
| Product information | External roll holder 1302920000 necessary |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ETIM 10.0 | EC001530 | ECLASS 14.0 | 27-28-11-02 |
| ECLASS 15.0 | 27-28-11-02 | | |

**Weidmüller**

## Drawings