

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The RockStar® HighPower system, with its completely newly developed and coordinated components in three and four pin versions, represents a novel product solution for pluggable energy transmission – failure-free

The RockStar® HighPower system has a modular design and offers the customer a multitude of product solutions for all kinds of application sites and requirements. The RockStar® HighPower end-wall connector is impact-resistant, water and dust-proof and was built to comply with DIN EN 61373 CAT 1b (bogie) requirements. The overall structure has been adapted to the confined space of wagon-to-wagon coupling - small, light and powerful

General ordering data

| Version | RockStar® HDC kits-Heavy-duty connectors, Plug- in connector, HighPower, 1500 V, 550 A, diecast aluminium, Plug housing |
|------------|---|
| Order No. | <u>1506860000</u> |
| Туре | HDC HP550 KIT 4M120 |
| GTIN (EAN) | 4050118315233 |
| Qty. | 1 items |

1

Catalogue status / Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

| Δn | nro | vals | |
|----|-----|------|--|
| Αþ | μιυ | vais | |

| ROHS Conform | | | |
|--------------|------|---------|--|
| | ROHS | Conform | |

Dimensions and weights

Net weight 3112 g

Temperatures

Limit temperature -40 °C ... 120 °C

Environmental Product Compliance

| RoHS Compliance Status | Compliant with exemption |
|--------------------------------------|--------------------------------------|
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | a1b198df-2a58-40a5-bb31-ff1a2bb12993 |

General data

| Number of poles | 4 | Type of connection | Crimp connection |
|--------------------------------------|--------------------------------|------------------------------|------------------|
| Design of housing | Plug housing | UL 94 flammability rating | V-0 |
| Colour | black (similar to RAL 9005) | Surface finish | Powder coating |
| Series | HighPower | Rated voltage (DIN EN 61984) | 1500 V |
| Rated impulse voltage (DIN EN 61984) | 10 kV | Rated current (DIN EN 61984) | 550 A |
| Free from halogens | false | Protection degree | IP68 when locked |

General data

| Type of connection | Crimp connection | Colour | black (similar to RAL 9005) |
|-------------------------------|-------------------|---------------------|--------------------------------|
| Conductor cross-section, max. | 120 mm² | Surface finish | Powder coating |
| Enclosure material | Aluminium diecast | Series | HighPower |
| Material of gasket | EPDM | Material of contact | Copper alloy |

Important note

| Product information | Depending on the intended operation, internally generated voltages can superimpose the working |
|---------------------|--|
| | voltage and contain corresponding peaks. It is imperative to ensure that these peak voltages do |
| | not exceed the rated voltage. For applications outside of this specification, please contact us. |

Classifications

| ETIM 6.0 | EC002641 | ETIM 7.0 | EC002641 |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002641 | ETIM 9.0 | EC002641 |
| ETIM 10.0 | EC002641 | ECLASS 9.0 | 27-44-03-06 |
| ECLASS 9.1 | 27-44-01-90 | ECLASS 10.0 | 27-44-03-06 |
| ECLASS 11.0 | 27-44-03-06 | ECLASS 12.0 | 27-44-03-06 |
| ECLASS 13.0 | 27-44-03-06 | ECLASS 14.0 | 27-44-03-06 |
| ECLASS 15.0 | 27-44-03-06 | | |

Creation date 01.12.2025 04:24:16 MEZ

Catalogue status / Drawings 2



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

IP68 version acc. to EN 45545



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

General ordering data

| Туре | VGM40-MS68 20-32 BG | Version |
|-------------------|-----------------------------------|---|
| Order No. | 1193620000 | Heavy-duty connectors, Accessories, Cable glands, Brass, nickel- |
| GTIN (EAN) | 4032248976577 | plated |
| Qty. | 10 ST | |
| | | |
| Туре | VGM40-SS68 20-32 BG | Version |
| Type Order No. | VGM40-SS68 20-32 BG 1193590000 | Version Heavy-duty connectors, Accessories, Cable glands, Stainless steel |
| | | |

Accessories



Accessories especially suitable for the demands of wagon-to-wagon coupling have been developed for the HighPower end-wall connectors and thus significantly enhance the added value of the plug-in connectors. Easy-to-install coding pins ensure reverse polarity protection, plastic cover caps provide sufficient dust protection, while aluminium covers are designed to be absolutely water and dust-proof.

The accessories intelligently round off the overall system.

General ordering data

| Туре | HDC HP550 CP | Version |
|------------|-----------------------------------|------------------------|
| Order No. | <u>1475840000</u> | HDC enclosures |
| GTIN (EAN) | 4050118282511 | |
| Qty. | 200 ST | |
| | | |
| Type | HDC HP SUKA 1P 550A | Version |
| | HDC HP SUKA 1P 550A 1479130000 | Version HDC enclosures |
| | | |

Creation date 01.12.2025 04:24:16 MEZ

Catalogue status / Drawings 3



Weidmüller Interface GmbH & Co. KG

4

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Housings



The protective housing is manufactured from seawaterresistant aluminium using pressure die casting.

High standards of water and dust protection, as well as particularly high impact resistance, are the hallmarks of this housing series.

A sophisticated two-stage surface coating ensures years of reliability.

All screws, crimp contacts and other exterior accessory parts are made of corrosion-resistant stainless steel.

General ordering data

| Туре | HDC HP550 ABGH 1P | Version |
|-------------------|---------------------------------|--|
| Order No. | <u>1535420000</u> | HDC enclosures, 1500 V, 550 A, Number of poles: 1, Installation size: |
| GTIN (EAN) | 4050118339444 | 550 |
| Qty. | 1 ST | |
| | | |
| Туре | HDC HP550 ABGH BG | Version |
| Type Order No. | HDC HP550 ABGH BG 1475700000 | Version HDC enclosures, 1500 V, Screw connection, Installation size: 550 |
| | | |