

ZQV 4N/4 BL

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Cross-connector (terminal), Plugged, blue, 32 A, Number of poles: 4, Pitch in mm (P): 6.10, Insulated: Yes, Width: 22.1 mm
Order No.	1528120000
Type	ZQV 4N/4 BL
GTIN (EAN)	4050118332872
Qty.	60 items

ZQV 4N/4 BL

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals



RoHS

Conform

Dimensions and weights

Depth	27.95 mm
Height	2.8 mm
Width	22.1 mm
Net weight	2.87 g

Depth (inches)	1.1004 inch
Height (inches)	0.1102 inch
Width (inches)	0.8701 inch

Temperatures

Storage temperature	-25 °C...55 °C
Operating temperature	-60 °C...130 °C
Continuous operating temp., max.	130 °C

Ambient temperature	-5 °C...40 °C
Continuous operating temp., min.	-60 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Basic material	Wemid
UL 94 flammability rating	V-0

Colour	blue
--------	------

Additional technical data

Type of fixing	Plugged		
	Explosion-tested version	Yes	

Dimensions

Pitch in mm (P)	6.10 mm
-----------------	---------

General

Number of poles	4
-----------------	---

Rating data

Rated voltage	400 V		
	Nominal current	32 A	

Important note

Product information	Due to stability and temperature reasons it is only possible to break out 60% of contact elements. The usage of cross connectors reduces the rated voltage to 400V. The voltage is reduced to 25V if cut cross connection with blank cut edges are used.
---------------------	--

Classifications

ETIM 8.0	EC000489		
ETIM 10.0	EC000489	ETIM 9.0	EC000489
		ECLASS 14.0	27-25-03-03

ZQV 4N/4 BL

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 26
D-32758 Detmold
Germany

Technical data

www.weidmueller.com

ECLASS 15.0

27-25-03-03
