

IE-FCI-PWCB-3A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, Front-Com® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the Front-Com® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Version	FrontCom, Fuse, Fuse insert
Order No.	1543690000
Type	IE-FCI-PWCB-3A
GTIN (EAN)	4050118348859
Qty.	1 items

IE-FCI-PWCB-3A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (UR) E479289

Dimensions and weights

Net weight 37 g

Temperatures

Storage temperature Operating temperature

Installation temperature

Environmental Product Compliance

RoHS Compliance Status Compliant with exemption

RoHS Exemption (if applicable/known) 8bl

REACH SVHC No SVHC above 0.1 wt%

General data

Product type Fuse Insert type Fuse insert

General standards

Certificate No. (DNV) TAA000022B Certificate No. (UR) E479289

Technical data

Type of connection Flat-blade receptacles 6.5 mm Nominal current 3 A
 Resistance 0,069 Ω typ. Operating voltage 32 V DC, 250 V AC
 Current-carrying capacity 1.5 kVeff

Classifications

ETIM 8.0 EC001121 ETIM 9.0 EC001121
 ETIM 10.0 EC001121 ECLASS 14.0 27-44-03-90
 ECLASS 15.0 27-44-03-90