

WQB B/24




Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 24, Pitch in mm (P): 5.10, Insulated: Yes, Width: 123.22 mm	
Order No.	<u>1579060000</u>	
Туре	WQB B/24	
GTIN (EAN)	4008190188597	
Qty.	20 items	



WQB B/24



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conform	Conform		
2.5 mm	Donth (inches)	0.0984 inch	
		0.984 inch	
		4.8512 inch	
	viatri (inches)	4.0012 IIICII	
05.00 55.00	A 12	F.00. 40.00	
	Ambient temperature	-5 °C40 °C	
pliance			
Compliant without exemption			
No SVHC above 0.1 wt%			
tinned copper	Colour	black	
For the terminals			
when corouged in	Installation advise	Direct mounting	
	installation advice	Direct mounting	
140			
5.10 mm			
24	Installation advice	Direct mounting	
,		,	
800 V	Nominal current	24 A	
FC000489	FTIM 7 O	EC000489	
		EC000489	
		27-14-11-40	
		27-14-11-40	
		27-14-11-40	
		27-25-03-03	
		2, 20 00 00	
	Compliant without exem No SVHC above 0.1 wt9 tinned copper For the terminals when screwed in No 5.10 mm	Height (inches) Width (inches)	

Creation date 29.11.2025 02:23:07 MEZ

Catalogue status / Drawings 2