

**WKS 1/3**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Product image**

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

**General ordering data**

Version	Cross-connector (terminal), when screwed in, orange, 41 A, Number of poles: 3, Pitch in mm (P): 14.10, Insulated: Yes, Width: 6.1 mm
Order No.	<a href="#">1604290000</a>
Type	WKS 1/3
GTIN (EAN)	4008190164027
Qty.	50 items

**Technical data****Approvals**

RoHS	Conform
------	---------

**Dimensions and weights**

Depth	18.8 mm	Depth (inches)	0.7402 inch
Height	22 mm	Height (inches)	0.8661 inch
Width	6.1 mm	Width (inches)	0.2402 inch
Net weight	2.22 g		

**Temperatures**

Ambient temperature	-5 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Material data**

Basic material	Polyamide 66	Colour	orange
UL 94 flammability rating	V-2		

**System specifications**

Version	Cross-connector
---------	-----------------

**Additional technical data**

Type of fixing	when screwed in	Installation advice	Direct mounting
Explosion-tested version	No	Type of mounting	when screwed in

**Dimensions**

Pitch in mm (P)	14.10 mm
-----------------	----------

**General**

Number of poles	3	Installation advice	Direct mounting
Operating temperature range, max.	100 °C	Type of mounting	when screwed in

**Rating data**

Rated voltage	400 V	Nominal current	41 A
---------------	-------	-----------------	------

**Classifications**

ETIM 8.0	EC000489	ETIM 9.0	EC000489
ETIM 10.0	EC000489	ECLASS 14.0	27-25-03-03
ECLASS 15.0	27-25-03-03		