

# **BZT ZVL1.5**



Weidmüller Interface GmbH & Co. KG

1

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





The modular ZIA distribution system for simple signal wiring is based on stackable individual modules with proven tension spring connection technology. Thanks to the integrated cross-connection and the combination of socket and pin contacts, variable distribution strips can be flexibly assembled. The base elements are simply snapped onto TS35 DIN rails and are available in various designs for 3- and 4-wire connections. This allows the system to be configured individually and tailored to the specific application.

# **General ordering data**

Version	Z-series, Marker holder
Order No.	<u>1676610000</u>
Туре	BZT ZVL1.5
GTIN (EAN)	4008190460037
Qty.	100 items

Catalogue status / Drawings



# **BZT ZVL1.5**



# Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Approvals				
ROHS	Conform			
Dimensions and weights				
			0.00=1.1	
Depth	17.45 mm	Depth (inches)	0.687 inch	
Height	12.9 mm	Height (inches)	0.5079 inch	
Width	5 mm	Width (inches)	0.1968 inch	
Net weight	0.62 g			
Temperatures				
Storage temperature	-25 °C55 °C	Ambient temperature	-5 °C40 °C	
Operating temperature	-40 °C100 °C	Continuous operating temp., min.	-40 °C	
Continuous operating temp., max.	100 °C			
Environmental Product Com	pliance			
RoHS Compliance Status	Compliant without exem			
REACH SVHC	No SVHC above 0.1 wt%	No SVHC above 0.1 wt%		
Material data				
Basic material	Wemid	Colour	dark beige	
UL 94 flammability rating	V-0	Coloui	dark beige	
System specifications				
Version	For the terminals	End cover plate required	No	
Additional technical data				
		_ ,,,,		
Open sides Installation advice	right	Type of fixing	Plugged	
Type of mounting	Direct mounting Snap-on	Explosion-tested version	No	
Dimensions	опар оп			
Difficusions				
Pitch in mm (P)	5.00 mm			
General				
Installation advice	Direct mounting	Operating temperature range, max.	100 °C	
Operating temperature range, min.	-40 °C	Operating temperature range, max.	100 0	
Classifications				
•				
ETIM 8.0	EC002848	ETIM 9.0	EC002848	
ETIM 10.0	EC002848	ECLASS 14.0	27-14-11-92	
ECLASS 15.0	27-14-11-92			

Creation date 05.12.2025 08:29:06 MEZ

Catalogue status / Drawings 2

# **BZT ZVL1.5**



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

Type	DEK 5/5 MC NE WS	Version
Order No.	1609801044	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1000 ST	
Туре	WS 12/5 MC NE WS	Version
Type Order No.	WS 12/5 MC NE WS 1609860000	Version WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
• •		

### WS 12/5



### WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

### **General ordering data**

Туре	WS 12/5 MM WS	Version
Order No.	2007190000	WS, Terminal marker, 12 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392036	
Qty.	800 ST	

Creation date 05.12.2025 08:29:06 MEZ