DFFC .5-1.0 ZRV1.5

We offer a broad portfolio of mounting support for easy handling and supplementation of our products. From various tools to insulating sleeves and various screws, our components are matched to each other down to the last detail and thus facilitate assembly in compliance with the respective standards and protective regulations.

General ordering data

Version	Crimp contact (terminal), 1.5 mm²
Order No.	1705320000
Type	DFFC .5-1.0 ZRV1.5
GTIN (EAN)	4008190948566
Qty.	500 items

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Net weight	0.22 g

Temperatures

Ambient temperature	-5 °C...40 °C	Operating temperature	130 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Basic material	Plastic	Surface finish	tinned
Colour	silver		

System specifications

Version	for holding 0.5 ... 1.0 mm²

Additional technical data

Installation advice	Direct mounting

Conductors for clamping (rated connection)

Stripping length	6 mm	Type of connection	Crimp contact
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	1 mm²	Wire connection cross section, finely stranded, max.	1 mm²

General

Installation advice	Direct mounting	Surface finish	tinned

Rating data

Rated cross-section	1.5 mm²	Volume resistance according to IEC 60947-7-x	1.83 mΩ
Power loss in accordance with IEC 60947-7-x	0.56 W		

Classifications

ETIM 8.0	EC000796	ETIM 9.0	EC000796
ETIM 10.0	EC000796	ECLASS 14.0	27-44-02-04
ECLASS 15.0	27-44-02-04		

Creation date 18.03.2026 07:45:12 MEZ