Data sheet

THM WO 33.5/93.1 GE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Similar to illustration

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

Version	THM, Conductor and cable markers, 8 - 21.7 mm, 33.5 x 93.1 mm, yellow
Order No.	1774410000
Type	THM WO 33.5/93.1 GE
GTIN (EAN)	4032248148592
Qty.	1 items

THM WO 33.5/93.1 GE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Depth	0.03 mm	Depth (inches)	0.001 inch
Height	33.5 mm	Height (inches)	1.3189 inch
Width	93.1 mm	Width (inches)	3.6653 inch
Net weight	247.28 g		

Temperatures

Operating temperature range	-40...150 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

General data

Adhesive	Polyacrylate adhesive		
Material colour according to resistance code	4		
Type of printing	neutral		
Version	Self-adhesive		
Width	93.1 mm		
UL 94 flammability rating	V-0		
Operating temperature range, max.	150 °C		
Operating temperature range, min.	-40 °C		
Colour	yellow		
Halogen	No		
Basic material	Polyester film		
Printed characters	without		
Number of markers per packaging unit	Form of supply	Label reel	
Size of labelling field	33.5 x 25 mm		
compatible printer			
Number of markers per combination	1 Label reel = Conductor and cable markers		
Operating temperature range	-40...150 °C		
Number per roll	500		

Conductor and cable markers

Halogen	No	Conductor cross-section, max.	400 mm²
Conductor cross-section, min.	0.75 mm²	Conductor O.D., max.	21.7 mm
Conductor O.D., min.	8 mm	Text field width	33.5 mm
Text field height	25 mm	Conductor O.D.	8 - 21.7 mm
Cross-section for connected wire	0.75 - 400 mm²		

Classifications

ETIM 8.0	EC001530	ETIM 9.0	EC001530
ETIM 10.0	EC001530	ECLASS 14.0	27-28-11-02
ECLASS 15.0	27-28-11-02		

THM WO 33.5/93.1 GE

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings