

HDC S4 SAS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The MixMate series of connectors can simultaneously transmit high rated currents and voltages as well as signals. An axial screw can be used to secure the wire.
Axial screw connection / TOP connection

General ordering data

| | |
|------------|--|
| Version | HDC insert, Male, 1000 V, 40 A, Number of poles: 4, Axial screw connection, Installation size: 3 |
| Order No. | 1789990000 |
| Type | HDC S4 SAS |
| GTIN (EAN) | 4032248212057 |
| Qty. | 1 items |

HDC S4 SAS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



| | |
|-------------------------|----------------------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate No. (cURus) | E92202 |

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 51 mm | Depth (inches) | 2.0079 inch |
| Height | 41.3 mm | Height (inches) | 1.626 inch |
| Width | 34 mm | Width (inches) | 1.3386 inch |
| Net weight | 78.7 g | | |

Temperatures

| | |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | c4c4c9fc-7957-49de-b5fd-516c2623a8c3 |

| | | |
|---------------------|--------------------------|---------------------------|
| Chemical resistance | Substance | Acetone |
| | Chemical resistance | Resistant |
| | Substance | Ammonia, watery |
| | Chemical resistance | Conditionally resistant |
| | Substance | Petrol |
| | Chemical resistance | Resistant |
| | Substance | Benzene |
| | Chemical resistance | Resistant |
| | Substance | Diesel oil |
| | Chemical resistance | Conditionally resistant |
| | Substance | Acetic acid, concentrated |
| | Chemical resistance | Resistant |
| | Substance | Potassium hydroxide |
| | Chemical resistance | Conditionally resistant |
| | Substance | Methanol |
| | Chemical resistance | Conditionally resistant |
| | Substance | Motor oil |
| | Chemical resistance | Conditionally resistant |
| | Substance | Lye, diluted |
| | Chemical resistance | Resistant |
| Substance | Hydrochlorofluorocarbons | |
| Chemical resistance | Conditionally resistant | |
| Substance | Outdoor use | |
| Chemical resistance | Conditionally resistant | |

Dimensions

| | | | |
|----------------|---------|-------------------|-------|
| Width | 34 mm | Total length base | 51 mm |
| Height of plug | 41.3 mm | | |

HDC S4 SAS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

General data

| | | |
|---------------------------------------|---|-------|
| Number of poles | 4 | |
| Tightening torque | 0.5 Nm | |
| Plugging cycles, silver | ≥ 500 | |
| Plugging cycles, gold | ≥ 500 | |
| Type of connection | Axial screw connection | |
| Installation size | 3 | |
| UL 94 flammability rating | V-0 | |
| Volume resistance | ≤1 mΩ | |
| Colour | beige | |
| Insulation resistance | 1010 Ω | |
| Insulating material | PC glass-fibre reinforced (UL-listed and railway-certified) | |
| Insulating material group | IIIa | |
| Conductor cross-section | 10 mm ² | |
| Tightening torque, max. PE connection | 0.8 Nm | |
| Surface finish | Silver passivated | |
| Type | Male | |
| Pollution severity | 3 | |
| Tightening torque, min. PE connection | 0.5 Nm | |
| Basic material | Copper alloy | |
| Series | MixMate | |
| Rated voltage (DIN EN 61984) | 1000 V | |
| Rated voltage according to UL/CSA | 600 V AC/DC | |
| Rated impulse voltage (DIN EN 61984) | 8 kV | |
| Rated current (DIN EN 61984) | 40 A | |
| Rated current (UR) | Wire connection cross section AWG | AWG 8 |
| | Rated current | 10 A |
| Rated current (cUR) | Wire connection cross section AWG | AWG 8 |
| | Rated current | 40 A |
| Free from halogens | true | |
| Low smoke acc. DIN EN 45545-2 | Yes | |
| BG | 3 | |
| Number of power contacts | 4 | |

Connection data PE

| | | | |
|---------------------------------------|--------------------|---------------------------------------|--------------|
| Connection type PE | Screw connection | Blade size, slotted (PE connection) | SD 0.6 x 3.5 |
| Stripping length PE connection | 8 mm | Tightening torque, max. PE connection | 0.8 Nm |
| Tightening torque, min. PE connection | 0.5 Nm | Fixing screw | M 4 |
| Rated cross-section | 10 mm ² | Wire cross section, AWG (PE), min. | AWG 14 |
| Wire cross section, AWG (PE), max. | AWG 11 | | |

Power contact

| | | | |
|---|------------------------|---|--------------------|
| Type of connection, power contact | Axial screw connection | Number of poles, performance contact | 4 |
| Tightening torque, power contact, max. | 1.7 Nm | Tightening torque, power contact, min. | 1.1 Nm |
| Stripping length, performance contact | 8 mm | Clamping range, power contact, max. | 10 mm ² |
| Clamping range, power contact, min. | 2.5 mm ² | Rated voltage (DIN EN 61984), power contact | 1000 V |
| Rated impulse voltage (DIN EN 61984), power contact | 8 kV | Rated current (DIN EN 61984), power contact | 40 A |
| Hexagon socket | 2 mm | | |

HDC S4 SAS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Version

| | | | |
|--|------------------------|--|---------------------|
| Wire connection cross section AWG, max. | AWG 11 | Stripping length, rated connection | 8 mm |
| Type of connection | Axial screw connection | Installation size | 3 |
| Volume resistance | ≤1 mΩ | Wire connection cross section AWG, min. | AWG 14 |
| Wire cross-section, solid, max. | 10 mm ² | Wire cross-section, solid, min. | 2.5 mm ² |
| Wire connection cross section, finely stranded, max. | 10 mm ² | Wire connection cross section, finely stranded, min. | 2.5 mm ² |
| Conductor cross-section, max. | 10 mm ² | Conductor cross-section, min. | 2.5 mm ² |
| Surface finish | Silver passivated | Basic material | Copper alloy |
| BG | 3 | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000438 | ETIM 9.0 | EC000438 |
| ETIM 10.0 | EC000438 | ECLASS 14.0 | 27-44-02-05 |
| ECLASS 15.0 | 27-44-02-05 | | |

Drawings

