WQL 2 WF6-8

Product image

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

Version	Bolt-type screw terminals, Cross-connector, Number of poles: 2
Order No.	1808980000
Type	WQL 2 WF6-8
GTIN (EAN)	4032248294701
Qty.	5 items

Creation date 22.12.2025 05:33:46 MEZ

WQL 2 WF6-8

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Depth	4 mm	Depth (inches)	0.1575 inch
Height	37 mm	Height (inches)	1.4567 inch
Width	20 mm	Width (inches)	0.7874 inch
Net weight	19.81 g		

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Basic material	Copper - zinc	Colour	grey

Additional technical data

Type of fixing	when screwed in	Explosion-tested version	No

Conductors for clamping (additional connection)

Terminal screw, additional connection	M 8

Conductors for clamping (rated connection)

Clamping screw	M 6

Dimensions

Pitch in mm (P)	22.00 mm

General

Number of poles	2

Rating data

Nominal current	150 A

Classifications

ETIM 8.0	EC000489	ETIM 9.0	EC000489
ETIM 10.0	EC000489	ECLASS 14.0	27-25-03-03
ECLASS 15.0	27-25-03-03		

Creation date 22.12.2025 05:33:46 MEZ