



SU 10.16HP/02/180SF 3.5AG BK BX

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Product image



Single-row, high-current male header, for side-by-side mounting without sacrificing any poles, or with patented flange for fast locking without tools. Maximum connection and operating reliability thanks to a mating profile that prevents incorrect connection, with unique coding diversity, additional fastening and integrable positioning aid. 3.5 mm pin length is optimised for wave soldering, plug-in direction 180° to solder pins.

General ordering data

| | |
|--------------|---|
| Version | PCB plug-in connector, male header, Screw/clip-on flange, THT solder connection, 10.16 mm, Number of poles: 2, 180°, Solder pin length (l): 3.5 mm, silver-plated, black, Box |
| Order No. | 1850880000 |
| Type | SU 10.16HP/02/180SF 3.5AG BK BX |
| GTIN (EAN) | 4032248381760 |
| Qty. | 42 items |
| Product data | IEC: 1000 V / 78.3 A UL: 300 V / 60 A |
| Packaging | Box |

SU 10.16HP/02/180SF 3.5AG BK BX

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (cURus) E60693

Dimensions and weights

| | | | |
|--------------------------|----------|-----------------|-------------|
| Depth | 13.6 mm | Depth (inches) | 0.5354 inch |
| Height | 35.5 mm | Height (inches) | 1.3976 inch |
| Height of lowest version | 32 mm | Width | 40.64 mm |
| Width (inches) | 1.6 inch | Net weight | 15.82 g |

Environmental Product Compliance

RoHS Compliance Status Compliant without exemption

REACH SVHC No SVHC above 0.1 wt%

System specifications

| | | | |
|--|---------------------------------------|---------------------|--|
| Product family | OMNIMATE Power - series BU/SU 10.16HP | | |
| Type of connection | Board connection | | |
| Mounting onto the PCB | THT solder connection | | |
| Pitch in mm (P) | 10.16 mm | | |
| Pitch in inches (P) | 0.400 " | | |
| Outgoing elbow | 180° | | |
| Number of poles | 2 | | |
| Number of solder pins per pole | 3 | | |
| Solder pin length (l) | 3.5 mm | | |
| Solder pin length tolerance | +0.1 / -0.3 mm | | |
| Solder pin dimensions | 1.2 x 1.1 mm | | |
| Solder pin dimensions = d tolerance | +0.1 / -0.1 mm | | |
| Solder eyelet hole diameter (D) | 1.6 mm | | |
| Solder eyelet hole diameter tolerance (D) | + 0,1 mm | | |
| L1 in mm | 10.16 mm | | |
| L1 in inches | 0.400 " | | |
| Number of rows | 1 | | |
| Pin series quantity | 1 | | |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch, plugged | | |
| Touch-safe protection acc. to DIN VDE 0470 | IP20 plugged | | |
| Volume resistance | 2.00 mΩ | | |
| Can be coded | Yes | | |
| Tightening torque for screw flange, min. | 0.3 Nm | | |
| Tightening torque for screw flange, max. | 0.4 Nm | | |
| Tightening torque | Torque type | Mounting screw, PCB | |
| | Usage information | Thickness | min. 1.44 mm |
| | | | max. 1.76 mm |
| | | Tightening torque | min. 0.25 Nm |
| | | | max. 0.3 Nm |
| | Recommended screw | Part number | SU 10.16 BFSC P 35X 14 |
| | | Thickness | min. 2.88 mm |

SU 10.16HP/02/180SF 3.5AG BK BX
Weidmüller Interface GmbH & Co. KG

 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com
Technical data

| | | | |
|-------------------|-------------|------|--|
| | | max. | 3.52 mm |
| Tightening torque | | min. | 0.2 Nm |
| | | max. | 0.25 Nm |
| Recommended screw | Part number | | SU 10.16 BFSC P 35X 14 |
| | | | |
| Thickness | | min. | 1.44 mm |
| | | max. | 3.52 mm |
| Tightening torque | | min. | 0.8 Nm |
| | | max. | 0.9 Nm |
| Recommended screw | Part number | | SU 10.16 BFSC S 35X12 |
| | | | |

Material data

| | | | |
|---------------------------------------|--------------|---------------------------------------|---------------|
| Insulating material | PBT GF | Colour | black |
| Colour chart (similar) | RAL 9011 | Insulating material group | IIIa |
| Comparative Tracking Index (CTI) | ≥ 200 | Insulation resistance | ≥ 108 Ω |
| Moisture Level (MSL) | | UL 94 flammability rating | V-0 |
| Contact material | Copper alloy | Contact surface | silver-plated |
| Layer structure of solder connection | ≥ 3 µm Ag | Layer structure of plug contact | ≥ 3 µm Ag |
| Storage temperature, min. | -40 °C | Storage temperature, max. | 70 °C |
| Operating temperature, min. | -50 °C | Operating temperature, max. | 120 °C |
| Temperature range, installation, min. | -25 °C | Temperature range, installation, max. | 120 °C |

Rated data acc. to IEC

| | | | |
|---|------------------------|---|-------------------|
| tested acc. to standard | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C) | 78.3 A |
| Rated current, max. number of poles (Tu=20°C) | 67.9 A | Rated current, min. number of poles (Tu=40°C) | 70.6 A |
| Rated current, max. number of poles (Tu=40°C) | 61.3 A | Rated voltage for surge voltage class / pollution degree II/2 | 1000 V |
| Rated voltage for surge voltage class / pollution degree III/2 | 1000 V | Rated voltage for surge voltage class / pollution degree III/3 | 690 V |
| Rated impulse voltage for surge voltage class/ pollution degree II/2 | 6 kV | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 8 kV |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 8 kV | Short-time withstand current resistance | 3 x 1s mit 1000 A |
| Creepage distance, min. | 10.5 mm | Clearance, min. | 8.9 mm |

Rated data acc. to CSA

| | | | |
|-----------------------------------|-------|-----------------------------------|-------|
| Rated voltage (Use group B / CSA) | 300 V | Rated voltage (Use group C / CSA) | 300 V |
| Rated voltage (Use group D / CSA) | 600 V | Rated current (Use group B / CSA) | 60 A |
| Rated current (Use group C / CSA) | 60 A | Rated current (Use group D / CSA) | 5 A |

Rated data acc. to UL 1059

| | | | |
|---------------------------------------|--------|---------------------------------------|--|
| Institute (cURus) | CURUS | Certificate No. (cURus) | E60693 |
| Rated voltage (Use group B / UL 1059) | 300 V | Rated voltage (Use group C / UL 1059) | 300 V |
| Rated voltage (Use group D / UL 1059) | 600 V | Rated voltage (Use group F / UL 1059) | 600 V |
| Rated current (Use group B / UL 1059) | 60 A | Rated current (Use group C / UL 1059) | 60 A |
| Rated current (Use group D / UL 1059) | 5 A | Creepage distance, min. | 10.5 mm |
| Clearance distance, min. | 8.9 mm | Reference to approval values | Specifications are maximum values, details - see approval certificate. |

SU 10.16HP/02/180SF 3.5AG BK BX

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Packing

| | | | |
|-----------|-----------|------------|-----------|
| Packaging | Box | VPE length | 215.00 mm |
| VPE width | 130.00 mm | VPE height | 77.00 mm |

Important note

| | |
|----------------|--|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request. |
| Notes | <ul style="list-style-type: none"> • Additional variants on request • Rated current related to rated cross-section & min. No. of poles. • P on drawing = pitch • Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards. • For all applications with flange we recommend to fix the pin header with the help of the soldering flange or a self-tapping screw on the board. • In accordance with IEC 61984, OMNIMATE-connectors are connectors without breaking capacity (COC). During designated use, connectors are not allowed to be engaged or disengaged when live or under load • Long term storage of the product with average temperature of 50 °C and maximum humidity 70%, 36 months |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002637 | ETIM 9.0 | EC002637 |
| ETIM 10.0 | EC002637 | ECLASS 14.0 | 27-46-02-01 |
| ECLASS 15.0 | 27-46-02-01 | | |


SU 10.16HP/02/180SF 3.5AG BK BX

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Drawings

Product image



Dimensional drawing



Example of use



SU 10.16HP/02/180SF 3.5AG BK BX

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Accessories

Coding elements



The pluggable connections for power electronics - optimised for modern drive technologies, e.g. motor starters, frequency converters and servo-controllers. OMNIMATE Power sets the new standard – with increased safety and innovative solutions such as the pluggable shield, integrated signal contacts and one-handed operation.

The three product lines offer you further advantages:

- Application-oriented scalability: from the compact 4 mm² connector for 29 A (IEC) or 20 A (UL) up to the sturdy 16 mm² connector for 76 A (IEC) or 54 A (UL)
- Unlimited usage up to 1,000 V (IEC) or 600 V (UL)
- A variety of application optimised mounting options

Our service:

Design your individual connectors simply by using the product configurator.

General ordering data

| | | | |
|------------|----------------------------|---|--|
| Type | KO BU/SU10.16HP BK | Version | |
| Order No. | 1824410000 | PCB plug-in connector, Accessories, Coding element, black, Number | |
| GTIN (EAN) | 4032248326716 | of poles: 1 | |
| Qty. | 50 ST | | |
| Type | KO BU/SU10.16HP WT | Version | |
| Order No. | 2592600000 | PCB plug-in connector, Accessories, Coding element, Natural, Number | |
| GTIN (EAN) | 4050118717389 | of poles: 1 | |
| Qty. | 50 ST | | |