Data sheet

# CLI C 1-6 GE/SW 63 CD

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Similar to illustration

CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm² to max. 70 mm². The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

## General ordering data

| | |
|---|---|
| Version | CableLine, Conductor and cable markers, 2.5 - 5 mm, 6 x 4.2 mm, yellow |
| Order No. | 1868811584 |
| Type | CLI C 1-6 GE/SW 63 CD |
| GTIN (EAN) | 4032248449132 |
| Qty. | 250 items |
| Delivery status | This article will no longer be available in the future. |
| Available until | 2025-08-31T00:00:00+02:00 |

# CLI C 1-6 GE/SW 63 CD

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Technical data

### Approvals

| | |
|---|---|
| ROHS | Conform |

### Dimensions and weights

| | | | |
|---|---|---|---|
| Depth | 5 mm | Depth (inches) | 0.1968 inch |
| Height | 6 mm | Height (inches) | 0.2362 inch |
| Width | 4.2 mm | Width (inches) | 0.1654 inch |
| Net weight | 0.15 g | | |

### Temperatures

| | |
|---|---|
| Operating temperature range | -30...80 °C |

### Environmental Product Compliance

| | |
|---|---|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

### General data

| | | | |
|---|---|---|---|
| Material colour according to resistance code | 4 | | |
| Orientation of print | horizontal | | |
| Type of printing | Standard | | |
| Printing method | hot-embossing | | |
| Version | CD | | |
| Width | 4.2 mm | | |
| UL 94 flammability rating | V-0 | | |
| Operating temperature range, max. | 80 °C | | |
| Operating temperature range, min. | -30 °C | | |
| Colour | yellow | | |
| Halogen | Yes | | |
| Insulation cross-section, max. | 5 | | |
| Basic material | PVC, soft, without Cadmium | | |
| Colour of printing | black | | |
| Printed characters | Numbers | | |
| Number of markers per packaging unit | Form of supply | Reel | |
| Recommended industries | Process, Machinery | | |
| Number of markers per combination | 1 Reel = Conductor and cable markers | | |
| Operating temperature range | -30...80 °C | | |
| Imprint | 63 | | |

### Conductor and cable markers

| | | | |
|---|---|---|---|
| Halogen | Yes | Conductor cross-section, max. | 4 mm² |
| Conductor cross-section, min. | 1.5 mm² | Conductor O.D., max. | 5 mm |
| Conductor O.D., min. | 2.5 mm | Conductor O.D. | 2.5 - 5 mm |
| Cross-section for connected wire | 1.5 - 4 mm² | | |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ETIM 10.0 | EC001530 | ECLASS 9.0 | 27-40-04-01 |
| ECLASS 9.1 | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |

# CLI C 1-6 GE/SW 63 CD

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Technical data

| | | | |
|---|---|---|---|
| ECLASS 11.0 | 27-28-11-02 | ECLASS 12.0 | 27-28-11-02 |
| ECLASS 13.0 | 27-28-11-02 | ECLASS 14.0 | 27-28-11-02 |
| ECLASS 15.0 | 27-28-11-02 | | |

## CLI C 1-6 GE/SW 63 CD

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Drawings

Similar to illustration