

ETO SM 22/22 TRANSPAR.

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmuller.com



Similar to illustration

SM is a MultiCard marker for labelling control and signalling devices. The tags are clipped into the carriers or attached by means of the adhesive film already fitted to them. Customised tags can be created with the PrintJet CONNECT or Plotter marking systems.

- Users can quickly produce tags to suit their needs
- No need to stock expensive standard tags
- Highly resistant printing quality when using the PrintJet as a substitute for engraving
- For extreme demands, we recommend the ETO SM protective film
- Holders can be used for the 22-mm or 30-mm-diameter push-buttons from Siemens, ABB, Moeller and Télémécanique

For custom printing: Please send us a file of our labelling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | |
|------------|---|
| Version | SwitchMark, Protective cap, 22 x 22 mm, Transparent |
| Order No. | 1880720000 |
| Type | ETO SM 22/22 TRANSPAR. |
| GTIN (EAN) | 4032248480883 |
| Qty. | 10 items |

ETO SM 22/22 TRANSPAR.

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

ROHS Conform

Dimensions and weights

| | | | |
|------------|--------|-----------------|-------------|
| Depth | 0.2 mm | Depth (inches) | 0.0079 inch |
| Height | 22 mm | Height (inches) | 0.8661 inch |
| Width | 22 mm | Width (inches) | 0.8661 inch |
| Net weight | 12.6 g | | |

Temperatures

Operating temperature range -20...80 °C

Environmental Product Compliance

RoHS Compliance Status Compliant without exemption
 REACH SVHC No SVHC above 0.1 wt%

General data

| | | | |
|--------------------------------------|------------------------------|-----------|--|
| Adhesive | Permanent acrylic copolymer | | |
| Number per sheet | 112 | | |
| Version | Self-adhesive | | |
| Width | 22 mm | | |
| UL 94 flammability rating | HB | | |
| Operating temperature range, max. | 80 °C | | |
| Operating temperature range, min. | -20 °C | | |
| Colour | Transparent | | |
| Halogen | No | | |
| Basic material | Polyester film | | |
| Printed characters | without | | |
| Number of markers per packaging unit | Form of supply | MultiCard | |
| Number of markers per combination | 1 MultiCard = Protective cap | | |
| Operating temperature range | -20...80 °C | | |

Device markers

Halogen No

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC001288 | ETIM 9.0 | EC001288 |
| ETIM 10.0 | EC001288 | ECLASS 14.0 | 27-28-11-04 |
| ECLASS 15.0 | 27-28-11-04 | | |

ETO SM 22/22 TRANSPAR.

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings

www.weidmueller.com

