

SAIL-VSA-5.0U-230**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Weidmüller can supply valve plugs as connecting lines with M8/M12 plugs and one end without connector. The status of the valve plug is shown by an LED. The valve plugs have a protective circuit. The Weidmüller range includes valve plugs of type A, B and C to DIN and industry standards. Protection class IP 67 is fulfilled when screwed in. The outlet direction is also a decisive factor, therefore Weidmüller offers different versions.

General ordering data

| | |
|------------|---|
| Version | Valve cable (assembled), One end without connector - valve plug, Design A (18 mm), Cable length: 5 m, PUR, grey |
| Order No. | 1891000500 |
| Type | SAIL-VSA-5.0U-230 |
| GTIN (EAN) | 4032248473021 |
| Qty. | 1 items |

SAIL-VSA-5.0U-230**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Approvals**

Approvals



ROHS

Conform

Dimensions and weights

Net weight

162 g

Environmental Product Compliance

RoHS Compliance Status

Compliant without exemption

REACH SVHC

No SVHC above 0.1 wt%

Technical specifications for cable

| | | | |
|-----------------------------|-----------------|--------------------|----------------------|
| Cable length | 5 m | Sheathing colour | grey |
| Suitable for cable carriers | Yes | Core cross-section | 0.75 mm ² |
| Shielded | No | Halogen | No |
| Sheath material | PUR | Number of poles | 3 |
| Outside diameter | 4.6 mm ± 0.2 mm | | |

General technical data

| | | | |
|-------------------|--|------------------------------|---------------|
| Coding | Design A (18 mm) | Connection thread | Miscellaneous |
| Contact surface | tinned | LED | Yes |
| Version | One end without connector - valve plug | Contact material | CuZn |
| Nominal voltage | 230 V | Nominal current | 4 A |
| Protection degree | IP67, when screwed in | Temperature range of housing | -25...+80 °C |

Plug, left

| | |
|-----------|---|
| Plug left | Valve plug, Design A (18 mm), Number of poles: 3, IP67, Plastic, unshielded |
|-----------|---|

Plug, right

| | |
|------------|--------------------|
| Plug right | Free conductor end |
|------------|--------------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC001855 | ETIM 9.0 | EC001855 |
| ETIM 10.0 | EC001855 | ECLASS 14.0 | 27-06-03-12 |
| ECLASS 15.0 | 27-06-03-12 | | |

Drawings

Dimensioned drawing



Pole scheme



Wiring diagram

