

SAIL-VSA-10U-230**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Weidmüller can supply valve plugs as connecting lines with M8/M12 plugs and one end without connector. The status of the valve plug is shown by an LED. The valve plugs have a protective circuit. The Weidmüller range includes valve plugs of type A, B and C to DIN and industry standards. Protection class IP 67 is fulfilled when screwed in. The outlet direction is also a decisive factor, therefore Weidmüller offers different versions.

General ordering data

Version	Valve cable (assembled), One end without connector - valve plug, Design A (18 mm), Cable length: 10 m, PUR, grey
Order No.	1891001000
Type	SAIL-VSA-10U-230
GTIN (EAN)	4032248473038
Qty.	1 items

SAIL-VSA-10U-230

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform

Dimensions and weights

Net weight

288.64 g

Environmental Product Compliance

RoHS Compliance Status

Compliant without exemption

REACH SVHC

No SVHC above 0.1 wt%

Technical specifications for cable

Cable length

10 m

Suitable for cable carriers

Yes

Shielded

No

Sheath material

PUR

Outside diameter

4.6 mm ± 0.2 mm

Sheathing colour

grey

Core cross-section

0.75 mm²

Halogen

No

Number of poles

3

General technical data

Coding

Design A (18 mm)

Contact surface

tinned

Version

One end without
connector - valve plug

Connection thread

Miscellaneous

LED

Yes

Contact material

CuZn

Nominal voltage

230 V

Protection degree

IP67, when screwed in

Nominal current

4 A

All valve plugs are fitted with protective
circuits

Varistor

Temperature range of housing

-25...+80 °C

Classifications

ETIM 8.0

EC001855

ETIM 10.0

EC001855

ECLASS 15.0

27-06-03-12

ETIM 9.0

EC001855

ECLASS 14.0

27-06-03-12

Drawings

Dimensioned drawing



Pole scheme



Wiring diagram

