WSMC 26-30



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com







Similar to illustration

WSM is a complete marking system for cables, conductors, pipes and components - it offers permanent labelling in environments which no other marker is able to withstand. This product line consists of labelling plates, carriers and stainless steel cable ties – available individually or complete in the WSM Set and Service Box.

Advantages:

- · Sturdy embossed characters for maximum legibility
- Resistant to heat, cold, corrosion, acids, chemicals, fire,
- Individual and multi-character markings, can also be combined
- Quick installation
- · Ideal for outdoor applications
- Easy attachment with cable ties

General ordering data

Version	Stainless steel markers, Conductor and cable markers, 150 x 10 mm, silver
Order No.	<u>1912160000</u>
Туре	WSMC 26-30
GTIN (EAN)	4032248541201
Qty.	1 items

1



WSMC 26-30



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Aр	pr	ov	al	S
----	----	----	----	---

ROHS

Dimensions and weights			
Depth	0.5 mm	Depth (inches)	0.0197 inch
Height	150 mm	Height (inches)	5.9055 inch
Width	10 mm	Width (inches)	0.3937 inch

Conform

5 g

Temperatures

Net weight

Operating temperature range 500 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

General data

Orientation of print	horizontal	
Number per sheet	1	
Type of printing	To customer specification	
Width	10 mm	
Operating temperature range, max.	500 °C	
Colour	silver	
Basic material	Stainless steel 1.4404	
Printed characters	Mixed characters	
Number of characters	30	
Number of markers per packaging unit	Form of supply	Component part
Number of markers per combination	1 Component part = Conductor and cable market	ers
Operating temperature range	500 °C	

Classifications

EC001530	ETIM 7.0	EC001530
EC001530	ETIM 9.0	EC001530
EC001530	ECLASS 9.0	27-40-04-01
27-40-04-01	ECLASS 10.0	27-40-04-01
27-28-11-02	ECLASS 12.0	27-28-11-02
27-28-11-02	ECLASS 14.0	27-28-11-02
27-28-11-02		
	EC001530 EC001530 27-40-04-01 27-28-11-02 27-28-11-02	EC001530 ETIM 9.0 EC001530 ECLASS 9.0 27-40-04-01 ECLASS 10.0 27-28-11-02 ECLASS 12.0 27-28-11-02 ECLASS 14.0

Catalogue status / Drawings 2