Data sheet

PRH 2.5/4/1

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



The use of reducing sleeves simplifies the connection of conductors with smaller cross-sections. Conductors can be reliably inserted into the clamping point without the strands fraying. The use of a reducing sleeve centres the conductor in the entry point.

General ordering data

Version	P-series, Reducing sleeve
Order No.	1916410000
Type	PRH 2.5/4/1
GTIN (EAN)	4032248549412
Qty.	100 items
Delivery status	Discontinued
Last order date	2023-02-28T00:00:00+01:00
Alternative product	AAM 2.5 YE FLASH

Data sheet

PRH 2.5/4/1

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Depth	12.5 mm	Depth (inches)	0.4921 inch
Height	6.8 mm	Height (inches)	0.2677 inch
Width	6.16 mm	Width (inches)	0.2425 inch
Net weight	0.19 g		

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Basic material	Wemid	Colour	grey
UL 94 flammability rating	V-0		

System specifications

Version	For the terminals

Additional technical data

Installation advice	Direct mounting

General

Installation advice	Direct mounting

Classifications

ETIM 8.0	EC002848	ETIM 9.0	EC002848
ETIM 10.0	EC002848	ECLASS 14.0	27-25-03-90
ECLASS 15.0	27-25-03-90		