


**SVZ 7.62HP/08/180SF SN BK BX SO**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Product image**


High-performance male header with the proven, 100% maintenance-free Weidmüller steel clamping yoke. Side-by-side mounting without sacrificing any poles or with patented multifunction flange for secure, fast fixing without tools. Maximum connection and operating reliability thanks to a mating profile that prevents incorrect connection, unique coding diversity, incorrect wiring protection. Suitable for labelling.

**General ordering data**

|              |                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------|
| Version      | PCB plug-in connector, male plug, 7.62 mm, Number of poles: 8, 180°, Clamping yoke connection, Clamping range, max. : 6 mm², Box |
| Order No.    | <a href="#">1932020000</a>                                                                                                       |
| Type         | SVZ 7.62HP/08/180SF SN BK BX SO                                                                                                  |
| GTIN (EAN)   | 4032248582136                                                                                                                    |
| Qty.         | 50 items                                                                                                                         |
| Product data | IEC: 1000 V / 57 A / 0.2 - 10 mm²<br>UL: 600 V / 42 A / AWG 24 - AWG 8                                                           |
| Packaging    | Box                                                                                                                              |

## SVZ 7.62HP/08/180SF SN BK BX SO

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

## Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (cURus) E60693

## Dimensions and weights

|            |          |                 |             |
|------------|----------|-----------------|-------------|
| Depth      | 41.45 mm | Depth (inches)  | 1.6319 inch |
| Height     | 23.1 mm  | Height (inches) | 0.9094 inch |
| Width      | 76.2 mm  | Width (inches)  | 3 inch      |
| Net weight | 41.28 g  |                 |             |

## Environmental Product Compliance

RoHS Compliance Status Compliant without exemption

REACH SVHC No SVHC above 0.1 wt%

## System Parameters

|                                              |                                         |                                            |                   |
|----------------------------------------------|-----------------------------------------|--------------------------------------------|-------------------|
| Product family                               | OMNIMATE Power - series<br>BV/SV 7.62HP | Type of connection                         | Field connection  |
| Wire connection method                       | Clamping yoke connection                | Pitch in mm (P)                            | 7.62 mm           |
| Pitch in inches (P)                          | 0.300 "                                 | Conductor outlet direction                 | 180°              |
| Number of poles                              | 8                                       | L1 in mm                                   | 53.34 mm          |
| L1 in inches                                 | 2.100 "                                 | Number of rows                             | 1                 |
| Pin series quantity                          | 1                                       | Rated cross-section                        | 6 mm <sup>2</sup> |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch                  | Touch-safe protection acc. to DIN VDE 0470 | IP20 plugged      |
| Protection degree                            | IP20                                    | Volume resistance                          | 4.50 mΩ           |
| Can be coded                                 | Yes                                     | Stripping length                           | 12 mm             |
| Tightening torque for screw flange, min.     | 0.2 Nm                                  | Tightening torque for screw flange, max.   | 0.3 Nm            |
| Tightening torque, min.                      | 0.5 Nm                                  | Tightening torque, max.                    | 0.6 Nm            |
| Clamping screw                               | M 3                                     | Screwdriver blade                          | 0.6 x 3.5         |
| Plugging cycles                              | 25                                      |                                            |                   |

## Material data

|                                       |          |                                       |                    |
|---------------------------------------|----------|---------------------------------------|--------------------|
| Insulating material                   | PA GF    | Colour                                | black              |
| Colour chart (similar)                | RAL 9011 | Insulating material group             | II                 |
| Comparative Tracking Index (CTI)      | ≥ 500    | Insulation resistance                 | ≥ 108 Ω            |
| Moisture Level (MSL)                  |          | UL 94 flammability rating             | V-0                |
| Contact base material                 | Cu-alloy | Contact material                      | Cu-alloy           |
| Contact surface                       | tinned   | Layer structure of plug contact       | 4...6 µm Sn glossy |
| Storage temperature, min.             | -40 °C   | Storage temperature, max.             | 70 °C              |
| Operating temperature, min.           | -50 °C   | Operating temperature, max.           | 125 °C             |
| Temperature range, installation, min. | -25 °C   | Temperature range, installation, max. | 125 °C             |

## Conductors suitable for connection

|                      |                     |
|----------------------|---------------------|
| Clamping range, min. | 0.2 mm <sup>2</sup> |
| Clamping range, max. | 6 mm <sup>2</sup>   |

## SVZ 7.62HP/08/180SF SN BK BX SO

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

|                                                 |                                        |                              |                              |                             |       |
|-------------------------------------------------|----------------------------------------|------------------------------|------------------------------|-----------------------------|-------|
| Wire connection cross section AWG, min.         | AWG 22                                 |                              |                              |                             |       |
| Wire connection cross section AWG, max.         | AWG 8                                  |                              |                              |                             |       |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>                    |                              |                              |                             |       |
| Solid, max. H05(07) V-U                         | 6 mm <sup>2</sup>                      |                              |                              |                             |       |
| Flexible, min. H05(07) V-K                      | 0.5 mm <sup>2</sup>                    |                              |                              |                             |       |
| Flexible, max. H05(07) V-K                      | 10 mm <sup>2</sup>                     |                              |                              |                             |       |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.25 mm <sup>2</sup>                   |                              |                              |                             |       |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 6 mm <sup>2</sup>                      |                              |                              |                             |       |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.25 mm <sup>2</sup>                   |                              |                              |                             |       |
| w. wire end ferrule, DIN 46228 pt 1, max.       | 6 mm <sup>2</sup>                      |                              |                              |                             |       |
| Plug gauge in accordance with EN 60999 a x b; ø | 2.8 mm x 2.0 mm; 2.4 mm                |                              |                              |                             |       |
| Clampable conductor                             | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 0.5 mm <sup>2</sup>          |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 14 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H0,5/18 OR</a>   |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 1 mm <sup>2</sup>            |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 15 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H1,0/18 GE</a>   |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 1.5 mm <sup>2</sup>          |                             |       |
|                                                 |                                        | wire end ferrule             | Stripping length             | nominal                     | 15 mm |
|                                                 |                                        |                              | Recommended wire-end ferrule | <a href="#">H1,5/18D SW</a> |       |
|                                                 | Stripping length                       | nominal                      | 12 mm                        |                             |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H1,5/12</a>      |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 0.75 mm <sup>2</sup>         |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 14 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H0,75/18 W</a>   |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 2.5 mm <sup>2</sup>          |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 14 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H2,5/19D BL</a>  |                             |       |
|                                                 |                                        | Stripping length             | nominal                      | 12 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H2,5/12</a>      |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 4 mm <sup>2</sup>            |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 12 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H4,0/12</a>      |                             |       |
|                                                 |                                        | Stripping length             | nominal                      | 14 mm                       |       |
|                                                 |                                        | Recommended wire-end ferrule | <a href="#">H4,0/20D GR</a>  |                             |       |
|                                                 | Cross-section for conductor connection | Type                         | fine-wired                   |                             |       |
|                                                 |                                        | nominal                      | 6 mm <sup>2</sup>            |                             |       |
|                                                 | wire end ferrule                       | Stripping length             | nominal                      | 14 mm                       |       |

## SVZ 7.62HP/08/180SF SN BK BX SO

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

|  |  |                              |                            |
|--|--|------------------------------|----------------------------|
|  |  | Recommended wire-end ferrule | <a href="#">H6,0/20 SW</a> |
|  |  | Stripping length             | nominal 12 mm              |
|  |  | Recommended wire-end ferrule | <a href="#">H6,0/12</a>    |

|                |                                                                                                                                                                        |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reference text | The outside diameter of the plastic collar should not be larger than the pitch (P). Length of ferrules is to be chosen depending on the product and the rated voltage. |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Rated data acc. to IEC

|                                                                           |                        |                                                                       |                   |
|---------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------|-------------------|
| tested acc. to standard                                                   | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C)                         | 57 A              |
| Rated current, max. number of poles (Tu=20°C)                             | 41 A                   | Rated current, min. number of poles (Tu=40°C)                         | 41 A              |
| Rated current, max. number of poles (Tu=40°C)                             | 41 A                   | Rated voltage for surge voltage class / pollution degree II/2         | 1000 V            |
| Rated voltage for surge voltage class / pollution degree III/2            | 1000 V                 | Rated voltage for surge voltage class / pollution degree III/3        | 800 V             |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 6 kV                   | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 8 kV              |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 8 kV                   | Short-time withstand current resistance                               | 3 x 1s with 420 A |
| Creepage distance, min.                                                   | 13.8 mm                | Clearance, min.                                                       | 13.56 mm          |

## Rated data acc. to CSA

|                                   |                                                                        |                                   |                |
|-----------------------------------|------------------------------------------------------------------------|-----------------------------------|----------------|
| Institute (CSA)                   | CSA                                                                    | Certificate No. (CSA)             | 200039-1534443 |
| Rated voltage (Use group B / CSA) | 600 V                                                                  | Rated voltage (Use group C / CSA) | 600 V          |
| Rated voltage (Use group D / CSA) | 600 V                                                                  | Rated current (Use group B / CSA) | 35 A           |
| Rated current (Use group C / CSA) | 35 A                                                                   | Rated current (Use group D / CSA) | 5 A            |
| Wire cross-section, AWG, min.     | AWG 24                                                                 | Wire cross-section, AWG, max.     | AWG 10         |
| Reference to approval values      | Specifications are maximum values, details - see approval certificate. |                                   |                |

## Rated data acc. to UL 1059

|                                       |                                                                        |                                       |        |
|---------------------------------------|------------------------------------------------------------------------|---------------------------------------|--------|
| Institute (cURus)                     | CURUS                                                                  | Certificate No. (cURus)               | E60693 |
| Rated voltage (Use group B / UL 1059) | 600 V                                                                  | Rated voltage (Use group C / UL 1059) | 600 V  |
| Rated voltage (Use group D / UL 1059) | 600 V                                                                  | Rated current (Use group B / UL 1059) | 42 A   |
| Rated current (Use group C / UL 1059) | 42 A                                                                   | Rated current (Use group D / UL 1059) | 5 A    |
| Wire cross-section, AWG, min.         | AWG 24                                                                 | Wire cross-section, AWG, max.         | AWG 8  |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate. |                                       |        |

## Packing

|           |           |            |           |
|-----------|-----------|------------|-----------|
| Packaging | Box       | VPE length | 333.00 mm |
| VPE width | 150.00 mm | VPE height | 89.00 mm  |

## Type tests

|                              |            |                                                                                  |
|------------------------------|------------|----------------------------------------------------------------------------------|
| Test: Durability of markings | Standard   | DIN EN 61984 section 7.3.2 / 09.02 taking pattern from DIN EN 60068-2-70 / 07.96 |
|                              | Test       | mark of origin, type identification, pitch, type of material                     |
|                              | Evaluation | available                                                                        |
|                              | Test       | durability                                                                       |
|                              | Evaluation | passed                                                                           |

## SVZ 7.62HP/08/180SF SN BK BX SO

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

|                                                           |                |                                                                                    |                              |
|-----------------------------------------------------------|----------------|------------------------------------------------------------------------------------|------------------------------|
| Test: Misengagement (Non-interchangeability)              | Standard       | DIN EN 61984 section 6.3 and 6.9.1 / 09.02, DIN EN 60512-13-5 / 11.08              |                              |
|                                                           | Test           | 180° turned with coding elements                                                   |                              |
|                                                           | Evaluation     | passed                                                                             |                              |
|                                                           | Test           | 180° turned without coding elements                                                |                              |
| Test: Clampable cross section                             | Evaluation     | passed                                                                             |                              |
|                                                           | Standard       | DIN EN 60999-1 section 7 and 9.1 / 12.00, DIN EN 60947-1 section 8.2.4.5.1 / 12.02 |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section                                      | solid 0.5 mm <sup>2</sup>    |
|                                                           |                | Type of conductor and conductor cross-section                                      | stranded 0.5 mm <sup>2</sup> |
|                                                           |                | Type of conductor and conductor cross-section                                      | solid 6 mm <sup>2</sup>      |
|                                                           |                | Type of conductor and conductor cross-section                                      | stranded 6 mm <sup>2</sup>   |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 24/1                     |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 24/19                    |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 10/1                     |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 10/19                    |
|                                                           | Evaluation     | passed                                                                             |                              |
|                                                           | Standard       | DIN EN 60999-1 section 7 and 9.1 / 12.00                                           |                              |
| Test for damage to and accidental loosening of conductors | Requirement    | 0.2 kg                                                                             |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section                                      | AWG 24/1                     |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 24/19                    |
|                                                           | Evaluation     | passed                                                                             |                              |
|                                                           | Requirement    | 0.3 kg                                                                             |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section                                      | solid 0.5 mm <sup>2</sup>    |
|                                                           |                | Type of conductor and conductor cross-section                                      | stranded 0.5 mm <sup>2</sup> |
|                                                           | Evaluation     | passed                                                                             |                              |
|                                                           | Requirement    | 1.4 kg                                                                             |                              |
|                                                           | Conductor type | Type of conductor and conductor cross-section                                      | solid 6 mm <sup>2</sup>      |
|                                                           |                | Type of conductor and conductor cross-section                                      | stranded 6 mm <sup>2</sup>   |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 10/1                     |
|                                                           |                | Type of conductor and conductor cross-section                                      | AWG 10/19                    |

## SVZ 7.62HP/08/180SF SN BK BX SO

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|               |                |                                               |                              |
|---------------|----------------|-----------------------------------------------|------------------------------|
| Pull-out test | Evaluation     | passed                                        |                              |
|               | Standard       | DIN EN 60999-1 section 9.5 / 12.00            |                              |
|               | Requirement    | ≥10 N                                         |                              |
|               | Conductor type | Type of conductor and conductor cross-section | AWG 24/1                     |
|               |                | Type of conductor and conductor cross-section | AWG 24/19                    |
|               | Evaluation     | passed                                        |                              |
|               | Requirement    | ≥20 N                                         |                              |
|               | Conductor type | Type of conductor and conductor cross-section | solid 0.5 mm <sup>2</sup>    |
|               |                | Type of conductor and conductor cross-section | stranded 0.5 mm <sup>2</sup> |
|               | Evaluation     | passed                                        |                              |
|               | Requirement    | ≥80 N                                         |                              |
|               | Conductor type | Type of conductor and conductor cross-section | solid 6 mm <sup>2</sup>      |
|               |                | Type of conductor and conductor cross-section | stranded 6 mm <sup>2</sup>   |
|               |                | Type of conductor and conductor cross-section | AWG 10/1                     |
|               |                | Type of conductor and conductor cross-section | AWG 10/19                    |
| Evaluation    | passed         |                                               |                              |

## Important note

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Notes          | <ul style="list-style-type: none"> <li>• Additional variants on request</li> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <li>• The data given under CSA relates to a cUL approval - E60693</li> <li>• P on drawing = pitch</li> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> <li>• In accordance with IEC 61984, OMNIMATE-connectors are connectors without breaking capacity (COC). During designated use, connectors are not allowed to be engaged or disengaged when live or under load</li> <li>• Long term storage of the product with average temperature of 50 °C and maximum humidity 70%, 36 months</li> </ul> |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC002638    | ETIM 9.0    | EC002638    |
| ETIM 10.0   | EC002638    | ECLASS 14.0 | 27-46-02-02 |
| ECLASS 15.0 | 27-46-02-02 |             |             |

## SVZ 7.62HP/08/180SF SN BK BX SO

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

## Drawings


### Product image




### Dimensional drawing




### Dimensional drawing



### Graph



### Graph



## SVZ 7.62HP/08/180SF SN BK BX SO

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Coding elements



The pluggable connections for power electronics - optimised for modern drive technologies, e.g. motor starters, frequency converters and servo-controllers. OMNIMATE Power sets the new standard – with increased safety and innovative solutions such as the pluggable shield, integrated signal contacts and one-handed operation.

The three product lines offer you further advantages:

- Application-oriented scalability: from the compact 4 mm<sup>2</sup> connector for 29 A (IEC) or 20 A (UL) up to the sturdy 16 mm<sup>2</sup> connector for 76 A (IEC) or 54 A (UL)
- Unlimited usage up to 1,000 V (IEC) or 600 V (UL)
- A variety of application optimised mounting options

Our service:

Design your individual connectors simply by using the product configurator.

## General ordering data

|            |                            |                                                                   |
|------------|----------------------------|-------------------------------------------------------------------|
| Type       | BV/SV 7.62HP KO            | Version                                                           |
| Order No.  | <a href="#">1937590000</a> | PCB plug-in connector, Accessories, Coding element, black, Number |
| GTIN (EAN) | 4032248608881              | of poles: 1                                                       |
| Qty.       | 50 ST                      |                                                                   |

## Strain reliefs



For frequent load changes: the "trailer coupling" for plug-in connectors.

The strain relief can do more than just relieve the strain on conductors:

Simply clip onto the plug and

- bundle conductors
- guide cables
- use as a connection and disconnection aid

No damage to the connecting points, clear, tidy wiring and easy to handle.

User advantages: permanent heavy-duty connections for harsh industrial environments and convenient operation ensure improved system availability.

## General ordering data

|            |                            |                                                                       |
|------------|----------------------------|-----------------------------------------------------------------------|
| Type       | BV/SV 7.62HP/02 ZE GR      | Version                                                               |
| Order No.  | <a href="#">1937550000</a> | PCB plug-in connector, Accessories, Strain relief, Light Grey, Number |
| GTIN (EAN) | 4032248608836              | of poles: 2                                                           |
| Qty.       | 50 ST                      |                                                                       |
| Type       | BV/SV 7.62HP/04 ZE GR      | Version                                                               |
| Order No.  | <a href="#">1937560000</a> | PCB plug-in connector, Accessories, Strain relief, Light Grey, Number |
| GTIN (EAN) | 4032248608843              | of poles: 4                                                           |
| Qty.       | 50 ST                      |                                                                       |