



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image















1







Female connector with integral cross-connection and clear printing for uninterrupted relaying of potential at full current-carrying capacity with the maximum cable cross-section. The cross-connection is positioned vertically between the poles of rows directly on top of each other. Conductor connection with tension clamp system with straight outlet and 3.5 mm pitch. Flange and release lever available. Packed in cardboard box.

General ordering data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS	Conform
UL File Number Search	<u>UL Website</u>
Certificate No. (UR)	E60693

Dimensions and weights

Depth	20.6 mm	Depth (inches)	0.811 inch
Height	15.7 mm	Height (inches)	0.6181 inch
Width	24.3 mm	Width (inches)	0.9567 inch
Net weight	4.14 g		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

System Parameters

Product family	OMNIMATE Signal - series B2L/S2L 3.50	- 2-row		
Type of connection	Field connection			
Wire connection method	Tension-clamp connection			
Pitch in mm (P)	3.50 mm			
Pitch in inches (P)	0.138 "			
Conductor outlet direction	180°			
Number of poles	10			
L1 in mm	14.00 mm			
L1 in inches	0.551 "			
Number of rows	1			
Pin series quantity	2			
Rated cross-section	1 mm ²			
Touch-safe protection acc. to DIN VDE 57 106	Safe from finger touch			
Touch-safe protection acc. to DIN VDE 0470	IP20 plugged/ IP10 unplugged			
Protection degree	IP20, when fully mounted			
Can be coded	Yes			
Stripping length	7 mm			
Screwdriver blade	0.4 x 2.5			
Screwdriver blade standard	DIN 5264			
Plugging cycles	25			
Plugging force/pole, max.	5 N			
Pulling force/pole, max.	4 N			
Tightening torque	Torque type	Screw flange		
	Usage information	Tightening torque	min.	0.15 Nm
			max.	0.2 Nm

Material data

Insulating material	PBT	Colour	black	
Colour chart (similar)	RAL 9011	Insulating material group	IIIa	

Creation date 30.11.2025 04:23:14 MEZ



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Comparative Tracking Index (CTI)	≥ 200	Moisture Level (MSL)	
UL 94 flammability rating	V-0	Contact material	Cu-alloy
Contact surface	tinned	Storage temperature, min.	-40 °C
Storage temperature, max.	70 °C	Operating temperature, min.	-50 °C
Operating temperature, max.	100 °C	Temperature range, installation, min.	-30 °C
Temperature range, installation, max.	100 °C		

Conductors suitable for connection

Conductors suitable for com	icction		
Clamping range, min.	0.08 mm ²		
Clamping range, max.	1 mm²		
Wire connection cross section AWG,	AWG 28		
min.			
Wire connection cross section AWG,	AWG 18		
max.			
Solid, min. H05(07) V-U	0.2 mm ²		
Solid, max. H05(07) V-U	1 mm ²		
Flexible, min. H05(07) V-K	0.2 mm ²		
Flexible, max. H05(07) V-K	1 mm²		
w. plastic collar ferrule, DIN 46228 pt	4, 0.14 mm ²		
min.			
w. plastic collar ferrule, DIN 46228 pt	4, 0.34 mm ²		
max.			
w. wire end ferrule, DIN 46228 pt 1,	0.14 mm ²		
min.			
w. wire end ferrule, DIN 46228 pt 1,	0.34 mm ²		
max.		_	
Clampable conductor	Cross-section for conductor connection	Туре	fine-wired
		nominal	0.14 mm ²
	wire end ferrule	Stripping length	nominal 10 mm
		Recommended wire- end ferrule	H0,14/12 GR SV
	Cross-section for conductor connection	Туре	fine-wired
		nominal	0.25 mm ²
	wire end ferrule	Stripping length	nominal 10 mm
		Recommended wire-	H0,25/12 HBL

Reference text

The outside diameter of the plastic collar should not be larger than the pitch (P), Length of ferrules is to be chosen depending on the product and the rated voltage.

end ferrule

Rated data acc. to IEC

tested acc. to standard	IEC 60664-1, IEC 61984	Rated current, min. number of poles (Tu=20°C)	10.6 A
Rated current, max. number of poles (Tu=20°C)	8.2 A	Rated current, min. number of poles (Tu=40°C)	9.1 A
Rated current, max. number of poles (Tu=40°C)	7 A	Rated voltage for surge voltage class / pollution degree II/2	200 V
Rated voltage for surge voltage class / pollution degree III/2	160 V	Rated voltage for surge voltage class / pollution degree III/3	80 V
Rated impulse voltage for surge voltage class/ pollution degree II/2	2.5 kV	Rated impulse voltage for surge voltage class/ pollution degree III/2	2.5 kV
Rated impulse voltage for surge voltage class/ contamination degree III/3	1.5 kV	Short-time withstand current resistance	3 x 1s with 77 A

Rated data acc. to CSA

Institute (CSA)	CSA	Certificate No. (CSA)	200039-1488444
Rated voltage (Use group B / CSA)	300 V	Rated current (Use group B / CSA)	7 A

Creation date 30.11.2025 04:23:14 MEZ







Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Wire cross-section, AWG, min.	AWG 28	Wire cross-section, AWG, max.	AWG 18	
Reference to approval values	Specifications are maximum values, details - see approval certificate.			

Rated data acc. to UL 1059

Institute (UR)	UR	Certificate No. (UR)	E60693
Rated voltage (Use group B / UL 1059)	150 V	Rated voltage (Use group C / UL 1059)	50 V
Rated current (Use group B / UL 1059)	7 A	Rated current (Use group C / UL 1059)	7 A
Wire cross-section, AWG, min.	AWG 28	Wire cross-section, AWG, max.	AWG 18
Reference to approval values	Specifications are maximum values, details - see approval certificate.		

Packing

Packaging	Box	VPE length	348.00 mm
VPE width	138.00 mm	VPE height	31.00 mm

Type tests

Test: Durability of markings	Standard DIN EN 61984 section 7.3.2 / 09.02 taking		
rest. Durability of markings	Standard	pattern from DIN EN 60068-2-70 / 07.96	
	Test	mark of origin, type identification, rated cross- section, type of material	
	Evaluation	available	
	Test	durability	
	Evaluation	passed	
Test: Misengagement (Non- interchangeability)	Standard	DIN EN 61984 section 6.3 and 6.9.1 / 09.02, DIN IEC 60512-7 section 5 / 05.94	
	Test	180° turned without coding elements	
	Evaluation	passed	
	Test	visual examination	
	Evaluation	passed	
Test: Clampable cross section	Standard	DIN EN 60999-1 section 7 and 9.1 / 12.00, DII EN 60947-1 section 8.2.4.5.1 / 12.02	
	Conductor type	Type of conductor solid 0.2 mm ² and conductor cross-section	
		Type of conductor stranded 0.2 mm ² and conductor cross-section	
		Type of conductor solid 1.0 mm ² and conductor cross-section	
		Type of conductor stranded 1.0 mm ² and conductor cross-section	
		Type of conductor AWG 28/1 and conductor cross-section	
		Type of conductor AWG 28/19 and conductor cross-section	
		Type of conductor AWG 18/1 and conductor cross-section	
		Type of conductor AWG 18/19 and conductor cross-section	
	Evaluation	passed	





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Test for damage to and accidental oosening of conductors	Standard	DIN EN 60999-1 section 9.4 / 12.00	
loosening of conductors	Requirement Conductor type	0.2 kg Type of conductor AWG 28/1 and conductor cross- section	
		Type of conductor AWG 28/19 and conductor cross-section	
	Evaluation	passed	
	Requirement	0.3 kg	
	Conductor type	Type of conductor solid 0.5 mm ² and conductor cross-section	
		Type of conductor stranded 0.5 m and conductor cross-section	ım²
	Evaluation	passed	
	Requirement	0.4 kg	
	Conductor type	Type of conductor solid 1.0 mm ² and conductor cross-section	
		Type of conductor stranded 1.0 m and conductor cross-section	ım²
		Type of conductor AWG 18/1 and conductor cross-section	
		Type of conductor AWG 18/19 and conductor cross-section	
ull-out test	Evaluation Standard	passed DIN EN 60999-1 section 9.4 / 12.00	
	Requirement	≥5 N	
	Conductor type	Type of conductor AWG 28/1 and conductor cross-section	
		Type of conductor AWG 28/19 and conductor cross-section	
	Requirement	≥20 N	
	Conductor type	Type of conductor H05V-U0.5 and conductor cross-section	
		Type of conductor H05V-K0.5 and conductor cross-section	
	Requirement	≥35 N	
	Conductor type	Type of conductor H05V-U1 and conductor cross-section	
		Type of conductor H05V-K1 and conductor cross-section	
		Type of conductor AWG 18/1 and conductor cross-section	
		Type of conductor AWG 18/19 and conductor cross-section	
	Requirement	≥30 N	
	Conductor type	Type of conductor AWG 18/1 and conductor cross-section	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Type of conductor and conductor cross-section

AWG 18/19

Important note

IPC conformity

Notes

Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.

Additional variants on request

- · Gold-plated contact surfaces on request
- Rated current related to rated cross-section & min. No. of poles.
- Wire end ferrule with plastic collar to DIN 46228/4
- Wire end ferrule without plastic collar to DIN 46228/1
- P on drawing = pitch
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.
- Crimp shape A for wire-end ferrules with crimping tools PZ 1,5 (order no. 9005990000) or PZ 6/5 (order no. 9011460000) for larger wire cross-sections recommended.
- In accordance with IEC 61984, OMNIMATE-connectors are connectors without breaking capacity (COC). During designated use, connectors are not allowed to be engaged or disengaged when live or under load
- Long term storage of the product with average temperature of 50 °C and maximum humidity 70%, 36 months

Classifications

ETIM 6.0	EC002638	ETIM 7.0	EC002638
ETIM 8.0	EC002638	ETIM 9.0	EC002638
ETIM 10.0	EC002638	ECLASS 9.0	27-44-03-09
ECLASS 9.1	27-44-03-09	ECLASS 10.0	27-44-03-09
ECLASS 11.0	27-46-02-02	ECLASS 12.0	27-46-02-02
ECLASS 13.0	27-46-02-02	ECLASS 14.0	27-46-02-02
ECLASS 15.0	27-46-02-02		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany


www.weidmueller.com

Drawings

Product image



Dimensional drawing



Graph

