

**PAC-S1500-SL24-AY0-1M5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

---

With increasing plant complexity, the obsolescence of certain PLCs and the relentless growth in demand for I / O signals, many installations or plants are having to replace existing controllers with new ones, without modifying existing field cabling. With the aid of adapters, pre-assembled cables and interfaces from Weidmüller the problem of replacing one PLC system with another can be solved easily and safely: users can maintain the existing field cabling, test the new system and keep installation downtimes to a minimum.

**General ordering data**

|            |                                        |
|------------|----------------------------------------|
|            |                                        |
| Order No.  | 2004540015                             |
| Type       | <a href="#">PAC-S1500-SL24-AY0-1M5</a> |
| GTIN (EAN) | 4099986595316                          |
| Qty.       | 1 items                                |

## PAC-S1500-SL24-AY0-1M5

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 418 g |
|------------|-------|

## Temperatures

|                       |  |
|-----------------------|--|
| Operating temperature |  |
|-----------------------|--|

## Environmental Product Compliance

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6c                                   |
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 4bbf2c0d-0764-4fc8-bb24-9351c28c190d |

## General Data

|                       |                        |                     |                                                |
|-----------------------|------------------------|---------------------|------------------------------------------------|
| Cable length          | 1.5 m                  | Basic material      | PVC                                            |
| Cable                 | Unshielded single-core | Interface connector | 2 x BLC 5.08/12/180R                           |
| Number of poles, min. | 20-pole                | Connector PLC side  | 2X SIEMENS S71500<br>6ES7592-1AM00-0XB0<br>40P |
| Wire cross-section    | 0.50 mm <sup>2</sup>   |                     |                                                |

## Electrical Data

|               |                     |
|---------------|---------------------|
| Rated voltage | ≤ 250 Vdc ≤ 250 Vac |
|---------------|---------------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC000237    | ETIM 9.0    | EC000237    |
| ETIM 10.0   | EC000237    | ECLASS 14.0 | 27-24-22-20 |
| ECLASS 15.0 | 27-24-22-20 |             |             |