



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration





Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

General ordering data

Version	Built-in plugs, M8, Mounting thread: M10, Number of poles: 4, Strand / cable length:
Order No.	<u>2423160000</u>
Туре	SAIE-M8S-4S-F9THR
GTIN (EAN)	4050118430127
Qty.	25 items

1



SAIE-M8S-4S-F9THR



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

ROHS Conform

Dimensions and weights

Net weight 7.15 g

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	Oea6d931-f9e9-40a6-89d9-8d67103189d3

Technical data of PCB plug-in connector

Number of poles	4	
Coding	M8 = none	
Type of mounting	Front mounting	
Housings	M8 pin	
Installation height	9 mm	
Housing surface	nickel-plated	
Shield connection	Yes	
Mounting thread	M10	
Nominal voltage	30 V	
Rated voltage	60 V (3-pole) / 30 V (4-,5- and 8-pole)	
Nominal current	4 A	
Rated current	4 A (3-, 4- and 5-pole) / 1.5 A (8-pole)	
Temperature range	-3080 °C	
Protection degree	IP67	
Contact surface	Au (Gold)	
Housing main material	CuZn, nickel-plated	
Connection thread	M8	
Tightening torque	M8: 0.5 Nm	
Mounting thread	M10	
Mounting torque range	0.8 Nm	
Mounting torque	max.	0.8 Nm
Mounting onto the PCB	THT/THR solder connection	
Insulation resistance	100 ΜΩ	
Pollution severity	3 (2 within the sealed area)	
Plugging cycles	≥ 100	
Contact material	Cu-alloy	
Seal material	NBR	
Lock nut material	Nickel-plated CuZn	
Material of the flange-mounted housing	Nickel-plated CuZn	
Grouting material	PUR	

General Info

Number of poles	4	Housing main material	CuZn, nickel-plated
Connection thread	M8	Contact material	Cu-alloy
Contact surface	Au (Gold)	Type of mounting	Front mounting
Protection degree	IP67	Plugging cycles	≥ 100

Creation date 30.11.2025 12:32:03 MEZ

Catalogue status / Drawings 2



SAIE-M8S-4S-F9THR



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Material data			
Contact material	Cu-alloy	Contact surface	Au (Gold)
System parameters			
Mounting onto the PCB	THT/THR solder	Number of poles	4
	connection	•	·
Pin series quantity	1	Insulation resistance	100 ΜΩ
Protection degree	IP67	Plugging cycles	≥ 100
Important note			
Important note Notes Classifications			
Notes			
Notes Classifications	EC002638	ETIM 7.0	EC003568
Notes	EC002638 EC003568	ETIM 7.0 ETIM 9.0	EC003568 EC003568
Notes Classifications ETIM 6.0			
Notes Classifications ETIM 6.0 ETIM 8.0 ETIM 10.0	EC003568	ETIM 9.0	EC003568
Notes Classifications ETIM 6.0 ETIM 8.0	EC003568 EC003568	ETIM 9.0 ECLASS 9.0	EC003568 27-44-03-09
Notes Classifications ETIM 6.0 ETIM 8.0 ETIM 10.0 ECLASS 9.1	EC003568 EC003568 27-44-03-09	ETIM 9.0 ECLASS 9.0 ECLASS 10.0	EC003568 27-44-03-09 27-44-03-09

Catalogue status / Drawings

SAIE-M8S-4S-F9THR




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany


www.weidmueller.com

Drawings

Dimensioned drawing



PCB design



Pole scheme

