



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Similar to illustration

Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

General ordering data

Version	Built-in plugs, M12, Mounting thread: , Number of
	poles: 8, Strand / cable length:
Order No.	<u>2423380000</u>
Туре	SAID-M12B-8S-9SMT
GTIN (EAN)	4050118431988
Qty.	25 items





Weidmüller Interface GmbH & Co. KG

EC003557

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals				
ROHS	Conform			
Dimensions and weights				
Net weight	3.84 g			
Environmental Product C	ompliance			
RoHS Compliance Status	Compliant with exemption	1		
RoHS Exemption (if applicable/kr		n) 6c		
REACH SVHC	Lead 7439-92-1			
SCIP	0ea6d931-f9e9-40a6-89	0ea6d931-f9e9-40a6-89d9-8d67103189d3		
Technical data of PCB plu	ıg-in connector			
Number of poles	8	Codina	A-coded	
Housings	M12 socket	Shield connection	Yes	
Nominal voltage	30 V	Rated voltage	250 V (4-pole) / 60 V (5-	
Normal voltage	30 v	nated voltage	pole) / 30 V (8-pole)	
Nominal current	2 A	Rated current	4 A (4- and 5-pole) / 2 A (8-pole)	
Temperature range	-2595 °C	Protection degree	IP67	
Contact surface	Au (Gold)	Housing main material	LCP	
Connection thread	M12	Tightening torque	M12: 0.8 Nm	
Pollution severity	3 (2 within the sealed area)	Plugging cycles	≥ 100	
Contact material	Cu-alloy	Lock nut material	Nickel-plated CuZn	
Material of the flange-mounted he	ousing Nickel-plated CuZn			
General Info				
Number of poles	8	UL 94 flammability rating	V-0	
Housing main material	LCP	Connection thread	M12	
Contact material	Cu-alloy	Contact surface	Au (Gold)	
Protection degree	IP67	Plugging cycles	≥ 100	
Material data				
UL 94 flammability rating	V-0	Contact material	Cu-alloy	
Contact surface	Au (Gold)			
System parameters				
Number of poles	8	Pin series quantity	1	
Protection degree	IP67	Plugging cycles	≥ 100	
Important note				
Notes				
Classifications				
ETIM 6.0	EC000438	ETIM 7.0	EC003557	
ETIM O O	FC000FF7	ETIMA O O	E0000EE7	

Creation date 26.11.2025 03:58:50 MEZ

ETIM 8.0

Catalogue status / Drawings 2

ETIM 9.0

EC003557





Weidmüller Interface GmbH & Co. KG

3

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

ETIM 10.0	EC003557	ECLASS 9.1	27-44-02-05
ECLASS 10.0	27-44-02-23	ECLASS 11.0	27-44-02-23
ECLASS 12.0	27-44-02-23	ECLASS 13.0	27-44-02-23
ECLASS 14.0	27-44-02-23	ECLASS 15.0	27-44-02-23

Catalogue status / Drawings



Drawings

SAID-M12B-8S-9SMT



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Dimensioned drawing	PCB design
	Pole scheme
	M12 = A-coded





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Accessories

Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

General ordering data

	Tonoral ordoning data		
Туре	SAIFG-M14X1-B-1	Version	
Order No.	2423920000	Built-in plug housing, M12 socket, Installation height: 9 mm	
GTIN (EAN)	4050118431803		
Qty.	25 ST		
Туре	SAIFG-M14X1-B-2	Version	
Order No.	2423950000	Built-in plug housing, M12 socket, Installation height: 13 mm	
GTIN (EAN)	4050118432336		
Qty.	25 ST		
Туре	SAIE-KMM14X1-SW15	Version	
Order No.	2424010000	Locknut	
GTIN (EAN)	4050118431230		
Qty.	25 ST		

Catalogue status / Drawings 5