

VGM40-MS68 EMC 20-32SET

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



The RockStar® HighPower housings are manufactured from high-strength die-cast aluminium and offer perfect protection against harsh environmental conditions thanks to continual optimisation. The multi-part housing gives users the opportunity to examine work processes down to the last step in the workflow.

General ordering data

Version	VG MS (standard brass cable gland)
Order No.	2457660000
Type	VGM40-MS68 EMC 20-32SET
GTIN (EAN)	4050118472752
Qty.	1 items

VGM40-MS68 EMC 20-32SET

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Dimensions and weights

Net weight	232 g
------------	-------

Temperatures

Limit temperature	-40 °C ... 130 °C
-------------------	-------------------

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	b5ff1f66-ddba-4739-9fc0-0521ddb52139

General data

Colour	silver	Basic material	Brass, nickel-plated
Free from halogens	true	Protection degree	IP68 - 15 bar

General data

Type of sealing	Sealing ring	Colour	silver
Cable diameter, max.	32 mm	Cable diameter, min.	20 mm
Cable gland	M 40, EMV	Basic material	Brass, nickel-plated

General information

Outer cable diameter, max.	32 mm	Outer cable diameter, min.	20 mm
O-Ring	NBR	Protection degree with GWDR	IP68
Operating temperature range, max.	130 °C	Operating temperature range, min.	-40 °C
Halogen	halogen-free	Standards	EN 45545-2:2013
AF size	45 mm	Protection degree	IP68 - 15 bar
Cable gland	M 40, EMV	Basic material	Brass, nickel-plated
External thread	M 40	Length of thread	7 mm

Important note

Product information	Depending on the intended operation, internally generated voltages can superimpose the working voltage and contain corresponding peaks. It is imperative to ensure that these peak voltages do not exceed the rated voltage. For applications outside of this specification, please contact us.
---------------------	---

Classifications

ETIM 8.0	EC000441	ETIM 9.0	EC000441
ETIM 10.0	EC000441	ECLASS 14.0	27-14-08-01
ECLASS 15.0	27-14-08-01		