

**VGM40L-MS68EMC 20-32SET****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The increasing sensitivity of electronic components and the increasing electromagnetic interference frequencies require cable glands to play an important role in the shielding concept of a system. This type of EMC cable glands are made for shielding against interference frequencies, with a 360° screening connection. A Finger-locking seal provides superior cable retention & strain relief, next to it, the cable gland meets the mechanical requirements of EN 62444. Due to the patented design a very easy and fast assembly will be possible.

**General ordering data**

Version	VG MS (standard brass cable gland)
Order No.	<a href="#">2498320000</a>
Type	VGM40L-MS68EMC 20-32SET
GTIN (EAN)	4050118511512
Qty.	1 items

**VGM40L-MS68EMC 20-32SET**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

ROHS Conform

**Dimensions and weights**

Net weight 1 g

**Temperatures**

Limit temperature -40 °C ... 130 °C

**Environmental Product Compliance**

RoHS Compliance Status Compliant with exemption  
 RoHS Exemption (if applicable/known) 6c  
 REACH SVHC Lead 7439-92-1  
 SCIP b5ff1f66-ddba-4739-9fc0-0521ddb52139

**General information**

Outer cable diameter, max.	32 mm	Outer cable diameter, min.	20 mm
O-Ring	NBR	Protection degree with GWDR	IP68
Operating temperature range, max.	130 °C	Operating temperature range, min.	-40 °C
Halogen	halogen-free	Standards	EN 45545-2:2013
AF size	45 mm	Protection degree	IP68 - 15 bar
Cable gland	M 40, EMV	Basic material	Brass, nickel-plated
External thread	M 40	Length of thread	7 mm

**Classifications**

ETIM 8.0	EC000441	ETIM 9.0	EC000441
ETIM 10.0	EC000441	ECLASS 14.0	27-14-08-01
ECLASS 15.0	27-14-08-01		