CABTITE SE 33-34 LRG BK



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Whether a large or small cable diameter – Cabtite always offers the right seal insert.

The conical shape of the sealing elements allows the previously positioned snap-in grid inlays to be pushed in easily from the inside to the outsid. It reliably seals intermediate spaces and provides strain relief in accordance with DIN EN 62444. The seal inserts combined with the frames achieve an IP 66 degree of protection. As a result of its slotted design with wave cut, it is especially suitable for pre-assembled cables.

- The black seal inserts are designed for a particularly high operating temperature and offer fire safety class UL 94 HB
- The grey sealing elements comply with fire safety class UL 94 VO and are therefore suitable for the demands of the railway industry
- By using multiple inserts, two or more cables, as well as special cables, can be passed through a sealing element

General ordering data

Version	Sealing element, Cabtite (cable entry system), TPE,		
	Deep black, Height: 42.8 mm, Width: 42.8 mm,		
	Depth: 17.7 mm, -40 °C120 °C, IP66		
Order No.	<u>2595510000</u>		
Туре	CABTITE SE 33-34 LRG BK		
GTIN (EAN)	4050118647075		
Qty.	. 10 items		

Catalogue status / Drawings



CABTITE SE 33-34 LRG BK



Weidmüller Interface GmbH & Co. KG

2

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Approvals					
Approvals					
ROHS	Conform				
Dimensions and weights					
Depth	17.7 mm	Depth (inches)	0.6968 inch		
Height	42.8 mm	Height (inches)	1.685 inch		
Width	42.8 mm	Width (inches)	1.685 inch		
Net weight	15.3 g				
Temperatures					
Operating temperature	-40 °C120 °C				
Environmental Product C	ompliance		'		
RoHS Compliance Status	Compliant without exemption				
REACH SVHC	No SVHC above 0.1 wt%				
General information					
Outer cable diameter, max.	34 mm	Outer cable diameter, min.	33 mm		
Silicone	No	UL 94 flammability rating	HB		
Halogen	No	Protection degree	IP66		
Basic material	TPE	Sealing element	1 large sealing element		
			. range seaming element		
Classifications					
ETIM 6.0	EC000879	ETIM 7.0	EC000879		
ETIM 8.0	EC000879	ETIM 9.0	EC000879		
ETIM 10.0	EC000879	ECLASS 9.0	27-14-44-21		
ECLASS 9.1	27-14-44-21	ECLASS 10.0	27-14-44-21		
ECLASS 11.0	27-14-44-21	ECLASS 12.0	27-14-08-07		
ECLASS 13.0	27-14-08-07	ECLASS 14.0	27-14-08-07		
ECLASS 15.0	27-14-08-07				

Catalogue status / Drawings