HDC HP550 GHDE CR 1P M32

The protective housing is manufactured from seawater-resistant aluminium using pressure die casting.
High standards of water and dust protection, as well as particularly high impact resistance, are the hallmarks of this housing series.
A sophisticated two-stage surface coating ensures years of reliability.
All screws, crimp contacts and other exterior accessory parts are made of corrosion-resistant stainless steel.

General ordering data

Version	, Installation size: 550
Order No.	2599790000
Type	HDC HP550 GHDE CR 1P M32
GTIN (EAN)	4064675049043
Qty.	1 items

HDC HP550 GHDE CR 1P M32

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals	$C \epsilon$
ROHS	Conform

Dimensions and weights

Net weight	84 g

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

General data

Design of housing	Bulkhead housing	Installation size	550
UL 94 flammability rating	None	Colour	black
Surface finish	Powder-coated	Free from halogens	false
BG	550	Protection degree	IP68, in plugged condition

General data

Colour	black	Surface finish	Powder-coated

Important note

Product information	Depending on the intended operation, internally generated voltages can superimpose the working voltage and contain corresponding peaks. It is imperative to ensure that these peak voltages do not exceed the rated voltage. For applications outside of this specification, please contact us.

Classifications

ETIM 8.0	EC000437	ETIM 9.0	EC000437
ETIM 10.0	EC000437	ECLASS 14.0	27-44-02-02
ECLASS 15.0	27-44-02-02		

HDC HP550 GHDE CR 1P M32

Drawings