

SQV 3/2**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

| | |
|------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Version | Cross-connector (terminal), when screwed in, black, grey, 41 A, Number of poles: 2, Pitch in mm (P): 9.00, Insulated: No, Width: 13 mm |
| Order No. | 2615030000 |
| Type | SQV 3/2 |
| GTIN (EAN) | 4050118653946 |
| Qty. | 100 items |

SQV 3/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 22.7 mm | Depth (inches) | 0.8937 inch |
| Height | 4.3 mm | Height (inches) | 0.1693 inch |
| Width | 13 mm | Width (inches) | 0.5118 inch |
| Net weight | 4.03 g | | |

Temperatures

| | | | |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Material data

| | | | |
|----------------|----|--------|-------------|
| Basic material | PA | Colour | black, grey |
|----------------|----|--------|-------------|

System specifications

| | |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

Additional technical data

| | | | |
|------------------|-----------------|--------------------------|----|
| Type of fixing | when screwed in | Explosion-tested version | No |
| Type of mounting | when screwed in | | |

Dimensions

| | |
|-----------------|---------|
| Pitch in mm (P) | 9.00 mm |
|-----------------|---------|

General

| | |
|-----------------|---|
| Number of poles | 2 |
|-----------------|---|

Rating data

| | |
|-----------------|------|
| Nominal current | 41 A |
|-----------------|------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |
| ETIM 10.0 | EC000489 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 | | |